

## Exam Questions DOP-C02

AWS Certified DevOps Engineer - Professional

<https://www.2passeasy.com/dumps/DOP-C02/>



### NEW QUESTION 1

A company's DevOps engineer uses AWS Systems Manager to perform maintenance tasks during maintenance windows. The company has a few Amazon EC2 instances that require a restart after notifications from AWS Health. The DevOps engineer needs to implement an automated solution to remediate these notifications. The DevOps engineer creates an Amazon EventBridge rule.

How should the DevOps engineer configure the EventBridge rule to meet these requirements?

- A. Configure an event source of AWS Health, a service of EC2, and an event type that indicates instance maintenance.
- B. Target a Systems Manager document to restart the EC2 instance.
- C. Configure an event source of Systems Manager and an event type that indicates a maintenance window.
- D. Target a Systems Manager document to restart the EC2 instance.
- E. Configure an event source of AWS Health, a service of EC2, and an event type that indicates instance maintenance.
- F. Target a newly created AWS Lambda function that registers an automation task to restart the EC2 instance during a maintenance window.
- G. Configure an event source of EC2 and an event type that indicates instance maintenance.
- H. Target a newly created AWS Lambda function that registers an automation task to restart the EC2 instance during a maintenance window.

**Answer: C**

#### Explanation:

AWS Health provides real-time events and information related to your AWS infrastructure. It can be integrated with Amazon EventBridge to act upon the health events automatically. If the maintenance notification from AWS Health indicates that an EC2 instance requires a restart, you can set up an EventBridge rule to respond to such events. In this case, the target of this rule would be a Lambda function that would trigger a Systems Manager automation to restart the EC2 instance during a maintenance window. Remember, AWS Health is the source of the events (not EC2 or Systems Manager), and AWS Lambda can be used to execute complex remediation tasks, such as scheduling maintenance tasks via Systems Manager.

The following are the steps involved in configuring the EventBridge rule to meet these requirements:

? Configure an event source of AWS Health, a service of EC2, and an event type that indicates instance maintenance.

? Target a newly created AWS Lambda function that registers an automation task to restart the EC2 instance during a maintenance window.

The AWS Lambda function will be triggered by the event from AWS Health. The function will then register an automation task to restart the EC2 instance during the next maintenance window.

### NEW QUESTION 2

A company wants to use AWS development tools to replace its current bash deployment scripts. The company currently deploys a LAMP application to a group of Amazon EC2 instances behind an Application Load Balancer (ALB). During the deployments, the company unit tests the committed application, stops and starts services, unregisters and re-registers instances with the load balancer, and updates file permissions. The company wants to maintain the same deployment functionality through the shift to using AWS services.

Which solution will meet these requirements?

- A. Use AWS CodeBuild to test the application.
- B. Use bash scripts invoked by AWS CodeDeploy's appspec.yml file to restart services, and deregister and register instances with the ALB.
- C. Use the appspec.yml file to update file permissions without a custom script.
- D. Use AWS CodePipeline to move the application from the AWS CodeCommit repository to AWS CodeDeploy.
- E. Use CodeDeploy's deployment group to test the application, unregister and re-register instances with the ALB, and restart service.
- F. and restart service.
- G. Use the appspec.yml file to update file permissions without a custom script.
- H. Use AWS CodePipeline to move the application source code from the AWS CodeCommit repository to AWS CodeDeploy.
- I. Use CodeDeploy to test the application.
- J. Use CodeDeploy's appspec.yml file to restart services and update permissions without a custom script.
- K. Use AWS CodeBuild to unregister and re-register instances with the ALB.
- L. Use AWS CodePipeline to trigger AWS CodeBuild to test the application.
- M. Use bash scripts invoked by AWS CodeDeploy's appspec.yml file to restart service.
- N. Unregister and re-register the instances in the AWS CodeDeploy deployment group with the ALB.
- O. Update the appspec.yml file to update file permissions without a custom script.

**Answer: D**

#### Explanation:

<https://aws.amazon.com/blogs/devops/how-to-test-and-debug-aws-codedeploy-locally-before-you-ship-your-code/#:~:text=You%20can%20test%20application%20code,local%20server%20or%20EC2%20instance.>

### NEW QUESTION 3

A DevOps engineer needs to apply a core set of security controls to an existing set of AWS accounts. The accounts are in an organization in AWS Organizations. Individual teams will administer individual accounts by using the AdministratorAccess AWS managed policy. For all accounts, AWS CloudTrail and AWS Config must be turned on in all available AWS Regions. Individual account administrators must not be able to edit or delete any of the baseline resources. However, individual account administrators must be able to edit or delete their own CloudTrail trails and AWS Config rules.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Create an AWS CloudFormation template that defines the standard account resource.
- B. Deploy the template to all accounts from the organization's management account by using CloudFormation StackSet.
- C. Set the stack policy to deny Update/Delete actions.
- D. Enable AWS Control Tower.
- E. Enroll the existing accounts in AWS Control Tower.
- F. Grant the individual account administrators access to CloudTrail and AWS Config.
- G. Designate an AWS Config management account.
- H. Create AWS Config recorders in all accounts by using AWS CloudFormation StackSet.
- I. Deploy AWS Config rules to the organization by using the AWS Config management account.
- J. Create a CloudTrail organization trail in the organization's management account.
- K. Deny modification or deletion of the AWS Config recorders by using an SCP.
- L. Create an AWS CloudFormation template that defines the standard account resource.

M. Deploy the template to all accounts from the organization's management account by using Cloud Formation StackSets Create an SCP that prevents updates or deletions to CloudTrail resources or AWS Config resources unless the principal is an administrator of the organization's management account.

**Answer:** D

#### NEW QUESTION 4

A company requires an RPO of 2 hours and an RTO of 10 minutes for its data and application at all times. An application uses a MySQL database and Amazon EC2 web servers. The development team needs a strategy for failover and disaster recovery. Which combination of deployment strategies will meet these requirements? (Select TWO.)

- A. Create an Amazon Aurora cluster in one Availability Zone across multiple Regions as the data store Use Aurora's automatic recovery capabilities in the event of a disaster
- B. Create an Amazon Aurora global database in two Regions as the data stor
- C. In the event of a failure promote the secondary Region as the primary for the application.
- D. Create an Amazon Aurora multi-master cluster across multiple Regions as the data stor
- E. Use a Network Load Balancer to balance the database traffic in different Regions.
- F. Set up the application in two Regions and use Amazon Route 53 failover-based routing that points to the Application Load Balancers in both Region
- G. Use health checks to determine the availability in a given Regio
- H. Use Auto Scaling groups in each Region to adjust capacity based on demand.
- I. Set up the application in two Regions and use a multi-Region Auto Scaling group behind Application Load Balancers to manage the capacity based on demand
- J. In the event of a disaster adjust the Auto Scaling group's desired instance count to increase baseline capacity in the failover Region.

**Answer:** BD

#### NEW QUESTION 5

An application runs on Amazon EC2 instances behind an Application Load Balancer (ALB). A DevOps engineer is using AWS CodeDeploy to release a new version. The deployment fails during the AllowTraffic lifecycle event, but a cause for the failure is not indicated in the deployment logs. What would cause this?

- A. The appspec
- B. .yml file contains an invalid script that runs in the AllowTraffic lifecycle hook.
- C. The user who initiated the deployment does not have the necessary permissions to interact with the ALB.
- D. The health checks specified for the ALB target group are misconfigured.
- E. The CodeDeploy agent was not installed in the EC2 instances that are part of the ALB target group.

**Answer:** C

#### Explanation:

This failure is typically due to incorrectly configured health checks in Elastic Load Balancing for the Classic Load Balancer, Application Load Balancer, or Network Load Balancer used to manage traffic for the deployment group. To resolve the issue, review and correct any errors in the health check configuration for the load balancer. <https://docs.aws.amazon.com/codedeploy/latest/userguide/troubleshooting-deployments.html#troubleshooting-deployments-allowtraffic-no-logs>

#### NEW QUESTION 6

A company is adopting AWS CodeDeploy to automate its application deployments for a Java-Apache Tomcat application with an Apache Webserver. The development team started with a proof of concept, created a deployment group for a developer environment, and performed functional tests within the application. After completion, the team will create additional deployment groups for staging and production. The current log level is configured within the Apache settings, but the team wants to change this configuration dynamically when the deployment occurs, so that they can set different log level configurations depending on the deployment group without having a different application revision for each group. How can these requirements be met with the LEAST management overhead and without requiring different script versions for each deployment group?

- A. Tag the Amazon EC2 instances depending on the deployment group
- B. Then place a script into the application revision that calls the metadata service and the EC2 API to identify which deployment group the instance is part of
- C. Use this information to configure the log level setting
- D. Reference the script as part of the AfterInstall lifecycle hook in the appspec.yml file.
- E. Create a script that uses the CodeDeploy environment variable DEPLOYMENT\_GROUP\_NAME to identify which deployment group the instance is part of
- F. Use this information to configure the log level setting
- G. Reference this script as part of the BeforeInstall lifecycle hook in the appspec.yml file.
- H. Create a CodeDeploy custom environment variable for each environment
- I. Then place a script into the application revision that checks this environment variable to identify which deployment group the instance is part of
- J. Use this information to configure the log level setting
- K. Reference this script as part of the ValidateService lifecycle hook in the appspec.yml file.
- L. Create a script that uses the CodeDeploy environment variable DEPLOYMENT\_GROUP\_ID to identify which deployment group the instance is part of to configure the log level setting
- M. Reference this script as part of the Install lifecycle hook in the appspec.yml file.

**Answer:** B

#### Explanation:

The following are the steps that the company can take to change the log level dynamically when the deployment occurs:

- ? Create a script that uses the CodeDeploy environment variable DEPLOYMENT\_GROUP\_NAME to identify which deployment group the instance is part of.
- ? Use this information to configure the log level settings.

? Reference this script as part of the BeforeInstall lifecycle hook in the appspec.yml file.

The DEPLOYMENT\_GROUP\_NAME environment variable is automatically set by CodeDeploy when the deployment is triggered. This means that the script does not need to call the metadata service or the EC2 API to identify the deployment group.

This solution is the least complex and requires the least management overhead. It also does not require different script versions for each deployment group.

The following are the reasons why the other options are not correct:

- ? Option A is incorrect because it would require tagging the Amazon EC2 instances, which would be a manual and time-consuming process.
- ? Option C is incorrect because it would require creating a custom environment variable for each environment. This would be a complex and error-prone process.
- ? Option D is incorrect because it would use the DEPLOYMENT\_GROUP\_ID environment variable. However, this variable is not automatically set by CodeDeploy, so the script would need to call the

metadata service or the EC2 API to get the deployment group ID. This would add complexity and overhead to the solution.

#### NEW QUESTION 7

A company uses AWS Key Management Service (AWS KMS) keys and manual key rotation to meet regulatory compliance requirements. The security team wants to be notified when any keys have not been rotated after 90 days.

Which solution will accomplish this?

- A. Configure AWS KMS to publish to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.
- B. Configure an Amazon EventBridge event to launch an AWS Lambda function to call the AWS Trusted Advisor API and publish to an Amazon Simple Notification Service (Amazon SNS) topic.
- C. Develop an AWS Config custom rule that publishes to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.
- D. Configure AWS Security Hub to publish to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.

**Answer:** C

#### Explanation:

<https://aws.amazon.com/blogs/security/how-to-use-aws-config-to-determine-compliance-of-aws-kms-key-policies-to-your-specifications/>

#### NEW QUESTION 8

A development team is using AWS CodeCommit to version control application code and AWS CodePipeline to orchestrate software deployments. The team has decided to use a remote main branch as the trigger for the pipeline to integrate code changes. A developer has pushed code changes to the CodeCommit repository, but noticed that the pipeline had no reaction, even after 10 minutes.

Which of the following actions should be taken to troubleshoot this issue?

- A. Check that an Amazon EventBridge rule has been created for the main branch to trigger the pipeline.
- B. Check that the CodePipeline service role has permission to access the CodeCommit repository.
- C. Check that the developer's IAM role has permission to push to the CodeCommit repository.
- D. Check to see if the pipeline failed to start because of CodeCommit errors in Amazon CloudWatch Logs.

**Answer:** A

#### Explanation:

When you create a pipeline from CodePipeline during the step-by-step it creates a CloudWatch Event rule for a given branch and repo like this:

```
{
  "source": [ "aws.codecommit"
],
  "detail-type": [
    "CodeCommit Repository State Change"
  ],
  "resources": [
    "arn:aws:codecommit:us-east-1:xxxxx:repo-name"
  ],
  "detail": {
    "event": [ "referenceCreated", "referenceUpdated"
  ],
  "referenceType": [ "branch"
  ],
  "referenceName": [ "master"
  ]
}
```

<https://docs.aws.amazon.com/codepipeline/latest/userguide/pipelines-trigger-source-repo-changes-console.html>

#### NEW QUESTION 9

A company is implementing a well-architected design for its globally accessible API stack. The design needs to ensure both high reliability and fast response times for users located in North America and Europe.

The API stack contains the following three tiers: Amazon API Gateway

AWS Lambda Amazon DynamoDB

Which solution will meet the requirements?

- A. Configure Amazon Route 53 to point to API Gateway APIs in North America and Europe using health check
- B. Configure the APIs to forward requests to a Lambda function in that Region
- C. Configure the Lambda functions to retrieve and update the data in a DynamoDB table in the same Region as the Lambda function.
- D. Configure Amazon Route 53 to point to API Gateway APIs in North America and Europe using latency-based routing and health check
- E. Configure the APIs to forward requests to a Lambda function in that Region
- F. Configure the Lambda functions to retrieve and update the data in a DynamoDB global table.
- G. Configure Amazon Route 53 to point to API Gateway in North America, create a disaster recovery API in Europe, and configure both APIs to forward requests to the Lambda functions in that Region
- H. Retrieve the data from a DynamoDB global table
- I. Deploy a Lambda function to check the North America API health every 5 minute
- J. In the event of a failure, update Route 53 to point to the disaster recovery API.
- K. Configure Amazon Route 53 to point to API Gateway API in North America using latency-based routing
- L. Configure the API to forward requests to the Lambda function in the Region nearest to the user
- M. Configure the Lambda function to retrieve and update the data in a DynamoDB table.

**Answer:** B

#### NEW QUESTION 10



A company has a data ingestion application that runs across multiple AWS accounts. The accounts are in an organization in AWS Organizations. The company needs to monitor the application and consolidate access to the application. Currently the company is running the application on Amazon EC2 instances from several Auto Scaling groups. The EC2 instances have no access to the internet because the data is sensitive. Engineers have deployed the necessary VPC endpoints. The EC2 instances run a custom AMI that is built specifically for the application. To maintain and troubleshoot the application, system administrators need the ability to log in to the EC2 instances. This access must be automated and controlled centrally. The company's security team must receive a notification whenever the instances are accessed. Which solution will meet these requirements?

- A. Create an Amazon EventBridge rule to send notifications to the security team whenever a user logs in to an EC2 instance. Use EC2 Instance Connect to log in to the instance.
- B. Deploy Auto Scaling groups by using AWS CloudFormation. Use the cfn-init helper script to deploy appropriate VPC routes for external access. Rebuild the custom AMI so that the custom AMI includes AWS Systems Manager Agent.
- C. Deploy a NAT gateway and a bastion host that has internet access. Create a security group that allows incoming traffic on all the EC2 instances from the bastion host. Install AWS Systems Manager Agent on all the EC2 instances. Use Auto Scaling group lifecycle hooks for monitoring and auditing access. Use Systems Manager Session Manager to log into the instances. Send logs to a log group in Amazon CloudWatch Log.
- D. Export data to Amazon S3 for auditing. Send notifications to the security team by using S3 event notifications.
- E. Use EC2 Image Builder to rebuild the custom AMI. Include the most recent version of AWS Systems Manager Agent in the image. Configure the Auto Scaling group to attach the AmazonSSMManagedInstanceCore role to all the EC2 instances. Use Systems Manager Session Manager to log in to the instances. Enable logging of session details to Amazon S3. Create an S3 event notification for new file uploads to send a message to the security team through an Amazon Simple Notification Service (Amazon SNS) topic.
- F. Use AWS Systems Manager Automation to build Systems Manager Agent into the custom AMI. Configure AWS Config to attach an SCP to the root organization account to allow the EC2 instances to connect to Systems Manager. Use Systems Manager Session Manager to log in to the instances. Enable logging of session details to Amazon S3. Create an S3 event notification for new file uploads to send a message to the security team through an Amazon Simple Notification Service (Amazon SNS) topic.

**Answer: C**

**Explanation:**

Even if AmazonSSMManagedInstanceCore is a managed policy and not an IAM role, I will go with C because this policy is to be attached to an IAM role for EC2 to access Systems Manager.

**NEW QUESTION 10**

A company uses AWS Organizations and AWS Control Tower to manage all the company's AWS accounts. The company uses the Enterprise Support plan. A DevOps engineer is using Account Factory for Terraform (AFT) to provision new accounts. When new accounts are provisioned, the DevOps engineer notices that the support plan for the new accounts is set to the Basic Support plan. The DevOps engineer needs to implement a solution to provision the new accounts with the Enterprise Support plan. Which solution will meet these requirements?

- A. Use an AWS Config conformance pack to deploy the account-part-of-organizations AWS Config rule and to automatically remediate any noncompliant accounts.
- B. Create an AWS Lambda function to create a ticket for AWS Support to add the account to the Enterprise Support plan.
- C. Grant the Lambda function the support:ResolveCase permission.
- D. Add an additional value to the control\_tower\_parameters input to set the AWSEnterpriseSupport parameter as the organization's management account number.
- E. Set the aft\_feature\_enterprise\_support feature flag to True in the AFT deployment input configuration.
- F. Redeploy AFT and apply the changes.

**Answer: D**

**Explanation:**

AWS Organizations is a service that helps to manage multiple AWS accounts. AWS Control Tower is a service that makes it easy to set up and govern secure, compliant multi-account AWS environments. Account Factory for Terraform (AFT) is an AWS Control Tower feature that provisions new accounts using Terraform templates. To provision new accounts with the Enterprise Support plan, the DevOps engineer can set the aft\_feature\_enterprise\_support feature flag to True in the AFT deployment input configuration. This flag enables the Enterprise Support plan for newly provisioned accounts.

<https://docs.aws.amazon.com/controltower/latest/userguide/aft-feature-options.html>

**NEW QUESTION 15**

A growing company manages more than 50 accounts in an organization in AWS Organizations. The company has configured its applications to send logs to Amazon CloudWatch Logs.

A DevOps engineer needs to aggregate logs so that the company can quickly search the logs to respond to future security incidents. The DevOps engineer has created a new AWS account for centralized monitoring.

Which combination of steps should the DevOps engineer take to make the application logs searchable from the monitoring account? (Select THREE.)

- A. In the monitoring account, download an AWS CloudFormation template from CloudWatch to use in Organization.
- B. Use CloudFormation StackSets in the organization's management account to deploy the CloudFormation template to the entire organization.
- C. Create an AWS CloudFormation template that defines an IAM role.
- D. Configure the role to allow logs.amazonaws.com to perform the logs:Link action if the aws:ResourceAccount property is equal to the monitoring account ID.
- E. Use CloudFormation StackSets in the organization's management account to deploy the CloudFormation template to the entire organization.
- F. Create an IAM role in the monitoring account.
- G. Attach a trust policy that allows logs.amazonaws.com to perform the iam:CreateSink action if the aws:PrincipalOrgId property is equal to the organization ID.
- H. In the organization's management account, enable the logging policies for the organization.
- I. Use CloudWatch Observability Access Manager in the monitoring account to create a sink.
- J. Allow logs to be shared with the monitoring account.
- K. Configure the monitoring account data selection to view the Observability data from the organization ID.
- L. In the monitoring account, attach the CloudWatchLogsReadOnlyAccess AWS managed policy to an IAM role that can be assumed to search the logs.

**Answer: BCF**

**Explanation:**

? To aggregate logs from multiple accounts in an organization, the DevOps engineer needs to create a cross-account subscription1 that allows the monitoring account to receive log events from the sharing accounts.

? To enable cross-account subscription, the DevOps engineer needs to create an IAM role in each sharing account that grants permission to CloudWatch Logs to link the log groups to the destination in the monitoring account<sup>2</sup>. This can be done using a CloudFormation template and StackSets<sup>3</sup> to deploy the role to all accounts in the organization.

? The DevOps engineer also needs to create an IAM role in the monitoring account that allows CloudWatch Logs to create a sink for receiving log events from other accounts<sup>4</sup>. The role must have a trust policy that specifies the organization ID as a condition.

? Finally, the DevOps engineer needs to attach the

CloudWatchLogsReadOnlyAccess policy<sup>5</sup> to an IAM role in the monitoring account that can be used to search the logs from the cross-account subscription.

References: 1: Cross-account log data sharing with subscriptions 2: Create an IAM role for CloudWatch Logs in each sharing account 3: AWS CloudFormation StackSets 4: Create an IAM role for CloudWatch Logs in your monitoring account 5: CloudWatchLogsReadOnlyAccess policy

#### NEW QUESTION 19

A company has an application and a CI/CD pipeline. The CI/CD pipeline consists of an AWS CodePipeline pipeline and an AWS CodeBuild project. The CodeBuild project runs tests against the application as part of the build process and outputs a test report. The company must keep the test reports for 90 days.

Which solution will meet these requirements?

- A. Add a new stage in the CodePipeline pipeline after the stage that contains the CodeBuild project
- B. Create an Amazon S3 bucket to store the report
- C. Configure an S3 deploy action type in the new CodePipeline stage with the appropriate path and format for the reports.
- D. Add a report group in the CodeBuild project buildspec file with the appropriate path and format for the report
- E. Create an Amazon S3 bucket to store the report
- F. Configure an Amazon EventBridge rule that invokes an AWS Lambda function to copy the reports to the S3 bucket when a build is complete
- G. Create an S3 Lifecycle rule to expire the objects after 90 days.
- H. Add a new stage in the CodePipeline pipeline
- I. Configure a test action type with the appropriate path and format for the report
- J. Configure the report expiration time to be 90 days in the CodeBuild project buildspec file.
- K. Add a report group in the CodeBuild project buildspec file with the appropriate path and format for the report
- L. Create an Amazon S3 bucket to store the report
- M. Configure the report group as an artifact in the CodeBuild project buildspec file
- N. Configure the S3 bucket as the artifact destination
- O. Set the object expiration to 90 days.

**Answer: B**

#### Explanation:

The correct solution is to add a report group in the AWS CodeBuild project buildspec file with the appropriate path and format for the reports. Then, create an Amazon S3 bucket to store the reports. You should configure an Amazon EventBridge rule that invokes an AWS Lambda function to copy the reports to the S3 bucket when a build is completed. Finally, create an S3 Lifecycle rule to expire the objects after 90 days. This approach allows for the automated transfer of reports to long-term storage and ensures

they are retained for the required duration without manual intervention<sup>1</sup>. References:

? AWS CodeBuild User Guide on test reporting<sup>1</sup>.

? AWS CodeBuild User Guide on working with report groups<sup>2</sup>.

? AWS Documentation on using AWS CodePipeline with AWS CodeBuild<sup>3</sup>.

#### NEW QUESTION 21

A company recently launched multiple applications that use Application Load Balancers. Application response time often slows down when the applications experience problems. A DevOps engineer needs to implement a monitoring solution that alerts the company when the applications begin to perform slowly. The DevOps engineer creates an Amazon Simple Notification Service (Amazon SNS) topic and subscribes the company's email address to the topic.

What should the DevOps engineer do next to meet the requirements?

- A. Create an Amazon EventBridge rule that invokes an AWS Lambda function to query the applications on a 5-minute interval. Configure the Lambda function to publish a notification to the SNS topic when the applications return errors.
- B. Create an Amazon CloudWatch Synthetics canary that runs a custom script to query the applications on a 5-minute interval.
- C. Configure the canary to use the SNS topic when the applications return errors.
- D. Create an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric. Configure the CloudWatch alarm to send a notification when the number of connections becomes greater than the configured number of threads that the application supports. Configure the CloudWatch alarm to use the SNS topic.
- E. Create an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric. Configure the CloudWatch alarm to send a notification when the average response time becomes greater than the longest response time that the application supports. Configure the CloudWatch alarm to use the SNS topic.

**Answer: B**

#### Explanation:

? Option A is incorrect because creating an Amazon EventBridge rule that invokes an AWS Lambda function to query the applications on a 5-minute interval is not a valid solution. EventBridge rules can only trigger Lambda functions based on events, not on time intervals. Moreover, querying the applications on a 5-minute interval might incur unnecessary costs and network overhead, and might not detect performance issues in real time.

? Option B is correct because creating an Amazon CloudWatch Synthetics canary that runs a custom script to query the applications on a 5-minute interval is a valid solution. CloudWatch Synthetics canaries are configurable scripts that monitor endpoints and APIs by simulating customer behavior. Canaries can run as often as once per minute, and can measure the latency and availability of the applications. Canaries can also send notifications to an Amazon SNS topic when they detect errors or performance issues<sup>1</sup>.

? Option C is incorrect because creating an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric is not a valid solution. The RequestCountPerTarget metric measures the number of requests completed or connections made per target in a target group<sup>2</sup>. This metric does not reflect the application response time, which is the requirement. Moreover, configuring the CloudWatch alarm to send a notification when the number of connections becomes greater than the configured number of threads that the application supports is not a valid way to measure the application performance, as it depends on the application design and implementation.

? Option D is incorrect because creating an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric is not a valid solution, for the same reason as option C. The RequestCountPerTarget metric does not reflect the application response time, which is the requirement. Moreover, configuring the CloudWatch alarm to send a notification when the average response time becomes greater than the longest response time that the application supports is not a valid way to measure the application performance, as it does not account for variability or outliers in the response time distribution.

References:

? 1: Using synthetic monitoring

? 2: Application Load Balancer metrics

#### NEW QUESTION 26

A DevOps engineer is deploying a new version of a company's application in an AWS CodeDeploy deployment group associated with its Amazon EC2 instances. After some time, the deployment fails. The engineer realizes that all the events associated with the specific deployment ID are in a Skipped status and code was not deployed in the instances associated with the deployment group.

What are valid reasons for this failure? (Select TWO.).

- A. The networking configuration does not allow the EC2 instances to reach the internet via a NAT gateway or internet gateway and the CodeDeploy endpoint cannot be reached.
- B. The IAM user who triggered the application deployment does not have permission to interact with the CodeDeploy endpoint.
- C. The target EC2 instances were not properly registered with the CodeDeploy endpoint.
- D. An instance profile with proper permissions was not attached to the target EC2 instances.
- E. The appspe
- F. yml file was not included in the application revision.

**Answer:** AD

#### Explanation:

<https://docs.aws.amazon.com/codedeploy/latest/userguide/troubleshooting-deployments.html#troubleshooting-skipped-lifecycle-events>

#### NEW QUESTION 28

A company runs a workload on Amazon EC2 instances. The company needs a control that requires the use of Instance Metadata Service Version 2 (IMDSv2) on all EC2 instances in the AWS account. If an EC2 instance does not prevent the use of Instance Metadata Service Version 1 (IMDSv1), the EC2 instance must be terminated.

Which solution will meet these requirements?

- A. Set up AWS Config in the account
- B. Use a managed rule to check EC2 instance
- C. Configure the rule to remediate the findings by using AWS Systems Manager Automation to terminate the instance.
- D. Create a permissions boundary that prevents the ec2:RunInstance action if the ec2:MetadataHttpTokens condition key is not set to a value of require
- E. Attach the permissions boundary to the IAM role that was used to launch the instance.
- F. Set up Amazon Inspector in the account
- G. Configure Amazon Inspector to activate deep inspection for EC2 instance
- H. Create an Amazon EventBridge rule for an Inspector2 finding
- I. Set an AWS Lambda function as the target to terminate the instance.
- J. Create an Amazon EventBridge rule for the EC2 instance launch successful event
- K. Send the event to an AWS Lambda function to inspect the EC2 metadata and to terminate the instance.

**Answer:** B

#### Explanation:

To implement a control that requires the use of IMDSv2 on all EC2 instances in the account, the DevOps engineer can use a permissions boundary. A permissions boundary is a policy that defines the maximum permissions that an IAM entity can have. The DevOps engineer can create a permissions boundary that prevents the ec2:RunInstance action if the ec2:MetadataHttpTokens condition key is not set to a value of required. This condition key enforces the use of IMDSv2 on EC2 instances. The DevOps engineer can attach the permissions boundary to the IAM role that was used to launch the instance. This way, any attempt to launch an EC2 instance without using IMDSv2 will be denied by the permissions boundary.

#### NEW QUESTION 30

A company has multiple member accounts that are part of an organization in AWS Organizations. The security team needs to review every Amazon EC2 security group and their inbound and outbound rules. The security team wants to programmatically retrieve this information from the member accounts using an AWS Lambda function in the management account of the organization.

Which combination of access changes will meet these requirements? (Choose three.)

- A. Create a trust relationship that allows users in the member accounts to assume the management account IAM role.
- B. Create a trust relationship that allows users in the management account to assume the IAM roles of the member accounts.
- C. Create an IAM role in each member account that has access to the AmazonEC2ReadOnlyAccess managed policy.
- D. Create an IAM role in each member account to allow the sts:AssumeRole action against the management account IAM role's ARN.
- E. Create an IAM role in the management account that allows the sts:AssumeRole action against the member account IAM role's ARN.
- F. Create an IAM role in the management account that has access to the AmazonEC2ReadOnlyAccess managed policy.

**Answer:** BCE

#### Explanation:

<https://aws.amazon.com/premiumsupport/knowledge-center/lambda-function-assume-iam-role/> <https://kreuzwerker.de/post/aws-multi-account-setups-reloaded>

#### NEW QUESTION 35

A DevOps engineer at a company is supporting an AWS environment in which all users use AWS IAM Identity Center (AWS Single Sign-On). The company wants to immediately disable credentials of any new IAM user and wants the security team to receive a notification.

Which combination of steps should the DevOps engineer take to meet these requirements? (Choose three.)

- A. Create an Amazon EventBridge rule that reacts to an IAM CreateUser API call in AWS CloudTrail.
- B. Create an Amazon EventBridge rule that reacts to an IAM GetLoginProfile API call in AWS CloudTrail.
- C. Create an AWS Lambda function that is a target of the EventBridge rule
- D. Configure the Lambda function to disable any access keys and delete the login profiles that are associated with the IAM user.
- E. Create an AWS Lambda function that is a target of the EventBridge rule
- F. Configure the Lambda function to delete the login profiles that are associated with the IAM user.
- G. Create an Amazon Simple Notification Service (Amazon SNS) topic that is a target of the EventBridge rule
- H. Subscribe the security team's group email address to the topic.



- I. Create an Amazon Simple Queue Service (Amazon SQS) queue that is a target of the Lambda function.
- J. Subscribe the security team's group email address to the queue.

**Answer:** ACE

#### NEW QUESTION 40

A company is launching an application. The application must use only approved AWS services. The account that runs the application was created less than 1 year ago and is assigned to an AWS Organizations OU.

The company needs to create a new Organizations account structure. The account structure must have an appropriate SCP that supports the use of only services that are currently active in the AWS account.

The company will use AWS Identity and Access Management (IAM) Access Analyzer in the solution.

Which solution will meet these requirements?

- A. Create an SCP that allows the services that IAM Access Analyzer identifies
- B. Create an OU for the account
- C. Move the account into the new OU
- D. Attach the new SCP to the new OU
- E. Detach the default FullAWSAccess SCP from the new OU.
- F. Create an SCP that denies the services that IAM Access Analyzer identifies
- G. Create an OU for the account
- H. Move the account into the new OU
- I. Attach the new SCP to the new OU.
- J. Create an SCP that allows the services that IAM Access Analyzer identifies
- K. Attach the new SCP to the organization's root.
- L. Create an SCP that allows the services that IAM Access Analyzer identifies
- M. Create an OU for the account
- N. Move the account into the new OU
- O. Attach the new SCP to the management account
- P. Detach the default FullAWSAccess SCP from the new OU.

**Answer:** A

#### Explanation:

To meet the requirements of creating a new Organizations account structure with an appropriate SCP that supports the use of only services that are currently active in the AWS account, the company should use the following solution:

? Create an SCP that allows the services that IAM Access Analyzer identifies. IAM Access Analyzer is a service that helps identify potential resource-access risks by analyzing resource-based policies in the AWS environment. IAM Access Analyzer can also generate IAM policies based on access activity in the AWS CloudTrail logs. By using IAM Access Analyzer, the company can create an SCP that grants only the permissions that are required for the application to run, and denies all other services. This way, the company can enforce the use of only approved AWS services and reduce the risk of unauthorized access<sup>12</sup>

? Create an OU for the account. Move the account into the new OU. An OU is a container for accounts within an organization that enables you to group accounts that have similar business or security requirements. By creating an OU for the account, the company can apply policies and manage settings for the account as a group. The company should move the account into the new OU to make it subject to the policies attached to the OU<sup>3</sup>

? Attach the new SCP to the new OU. Detach the default FullAWSAccess SCP from the new OU. An SCP is a type of policy that specifies the maximum permissions for an organization or organizational unit (OU). By attaching the new SCP to the new OU, the company can restrict the services that are available to all accounts in that OU, including the account that runs the application. The company should also detach the default FullAWSAccess SCP from the new OU, because this policy allows all actions on all AWS services and might override or conflict with the new SCP<sup>45</sup>

The other options are not correct because they do not meet the requirements or follow best practices. Creating an SCP that denies the services that IAM Access Analyzer identifies is not a good option because it might not cover all possible services that are not approved or required for the application. A deny policy is also more difficult to maintain and update than an allow policy. Creating an SCP that allows the services that IAM Access Analyzer identifies and attaching it to the organization's root is not a good option because it might affect other accounts and OUs in the organization that have different service requirements or approvals. Creating an SCP that allows the services that IAM Access Analyzer identifies and attaching it to the management account is not a valid option because SCPs cannot be attached directly to accounts, only to OUs or roots.

References:

- ? 1: Using AWS Identity and Access Management Access Analyzer - AWS Identity and Access Management
- ? 2: Generate a policy based on access activity - AWS Identity and Access Management
- ? 3: Organizing your accounts into OUs - AWS Organizations
- ? 4: Service control policies - AWS Organizations
- ? 5: How SCPs work - AWS Organizations

#### NEW QUESTION 45

A company has multiple accounts in an organization in AWS Organizations. The company's SecOps team needs to receive an Amazon Simple Notification Service (Amazon SNS) notification if any account in the organization turns off the Block Public Access feature on an Amazon S3 bucket. A DevOps engineer must implement this change without affecting the operation of any AWS accounts. The implementation must ensure that individual member accounts in the organization cannot turn off the notification.

Which solution will meet these requirements?

- A. Designate an account to be the delegated Amazon GuardDuty administrator account
- B. Turn on GuardDuty for all accounts across the organization
- C. In the GuardDuty administrator account, create an SNS topic
- D. Subscribe the SecOps team's email address to the SNS topic
- E. In the same account, create an Amazon EventBridge rule that uses an event pattern for GuardDuty findings and a target of the SNS topic.
- F. Create an AWS CloudFormation template that creates an SNS topic and subscribes the SecOps team's email address to the SNS topic
- G. In the template, include an Amazon EventBridge rule that uses an event pattern of CloudTrail activity for s3:PutBucketPublicAccessBlock and a target of the SNS topic
- H. Deploy the stack to every account in the organization by using CloudFormation StackSets.
- I. Turn on AWS Config across the organization
- J. In the delegated administrator account, create an SNS topic
- K. Subscribe the SecOps team's email address to the SNS topic
- L. Deploy a conformance pack that uses the s3-bucket-level-public-access-prohibited AWS Config managed rule in each account and uses an AWS Systems Manager document to publish an event to the SNS topic to notify the SecOps team.
- M. Turn on Amazon Inspector across the organization



- N. In the Amazon Inspector delegated administrator account, create an SNS topic.
- O. Subscribe the SecOps team's email address to the SNS topic.
- P. In the same account, create an Amazon EventBridge rule that uses an event pattern for public network exposure of the S3 bucket and publishes an event to the SNS topic to notify the SecOps team.

**Answer: C**

**Explanation:**

Amazon GuardDuty is primarily on threat detection and response, not configuration monitoring. A conformance pack is a collection of AWS Config rules and remediation actions that can be easily deployed as a single entity in an account and a Region or across an organization in AWS Organizations.  
<https://docs.aws.amazon.com/config/latest/developerguide/conformance-packs.html> <https://docs.aws.amazon.com/config/latest/developerguide/s3-account-level-public-access-blocks.html>

**NEW QUESTION 50**

A company has chosen AWS to host a new application. The company needs to implement a multi-account strategy. A DevOps engineer creates a new AWS account and an organization in AWS Organizations. The DevOps engineer also creates the OU structure for the organization and sets up a landing zone by using AWS Control Tower.

The DevOps engineer must implement a solution that automatically deploys resources for new accounts that users create through AWS Control Tower Account Factory. When a user creates a new account, the solution must apply AWS CloudFormation templates and SCPs that are customized for the OU or the account to automatically deploy all the resources that are attached to the account. All the OUs are enrolled in AWS Control Tower.

Which solution will meet these requirements in the MOST automated way?

- A. Use AWS Service Catalog with AWS Control Tower.
- B. Create portfolios and products in AWS Service Catalog.
- C. Grant granular permissions to provision these resources.
- D. Deploy SCPs by using the AWS CLI and JSON documents.
- E. Deploy CloudFormation stack sets by using the required template.
- F. Enable automatic deployments.
- G. Deploy stack instances to the required account.
- H. Deploy a CloudFormation stack set to the organization's management account to deploy SCPs.
- I. Create an Amazon EventBridge rule to detect the CreateManagedAccount event.
- J. Configure AWS Service Catalog as the target to deploy resources to any new account.
- K. Deploy SCPs by using the AWS CLI and JSON documents.
- L. Deploy the Customizations for AWS Control Tower (CfCT) solution.
- M. Use an AWS CodeCommit repository as the source.
- N. In the repository, create a custom package that includes the CloudFormation templates and the SCP JSON documents.

**Answer: D**

**Explanation:**

The CfCT solution is designed for the exact purpose stated in the question. It extends the capabilities of AWS Control Tower by providing you with a way to automate resource provisioning and apply custom configurations across all AWS accounts created in the Control Tower environment. This enables the company to implement additional account customizations when new accounts are provisioned via the Control Tower Account Factory. The CloudFormation templates and SCPs can be added to a CodeCommit repository and will be automatically deployed to new accounts when they are created. This provides a highly automated solution that does not require manual intervention to deploy resources and SCPs to new accounts.

**NEW QUESTION 51**

A DevOps engineer is creating an AWS CloudFormation template to deploy a web service. The web service will run on Amazon EC2 instances in a private subnet behind an Application Load Balancer (ALB). The DevOps engineer must ensure that the service can accept requests from clients that have IPv6 addresses.

What should the DevOps engineer do with the CloudFormation template so that IPv6 clients can access the web service?

- A. Add an IPv6 CIDR block to the VPC and the private subnet for the EC2 instance.
- B. Create route table entries for the IPv6 network, use EC2 instance types that support IPv6, and assign IPv6 addresses to each EC2 instance.
- C. Assign each EC2 instance an IPv6 Elastic IP address.
- D. Create a target group, and add the EC2 instances as target.
- E. Create a listener on port 443 of the ALB, and associate the target group with the ALB.
- F. Replace the ALB with a Network Load Balancer (NLB). Add an IPv6 CIDR block to the VPC and subnets for the NLB, and assign the NLB an IPv6 Elastic IP address.
- G. Add an IPv6 CIDR block to the VPC and subnets for the ALB.
- H. Create a listener on port 443, and specify the dualstack IP address type on the ALB.
- I. Create a target group, and add the EC2 instances as target.
- J. Associate the target group with the ALB.

**Answer: D**

**Explanation:**

It involves adding an IPv6 CIDR block to the VPC and subnets for the ALB and specifying the dualstack IP address type on the ALB listener. This allows the ALB to listen on both IPv4 and IPv6 addresses, and forward requests to the EC2 instances that are added as targets to the target group associated with the ALB.

**NEW QUESTION 55**

A company's application is currently deployed to a single AWS Region. Recently, the company opened a new office on a different continent. The users in the new office are experiencing high latency. The company's application runs on Amazon EC2 instances behind an Application Load Balancer (ALB) and uses Amazon DynamoDB as the database layer. The instances run in an EC2 Auto Scaling group across multiple Availability Zones. A DevOps engineer is tasked with minimizing application response times and improving availability for users in both Regions.

Which combination of actions should be taken to address the latency issues? (Choose three.)

- A. Create a new DynamoDB table in the new Region with cross-Region replication enabled.
- B. Create new ALB and Auto Scaling group global resources and configure the new ALB to direct traffic to the new Auto Scaling group.
- C. Create new ALB and Auto Scaling group resources in the new Region and configure the new ALB to direct traffic to the new Auto Scaling group.
- D. Create Amazon Route 53 records, health checks, and latency-based routing policies to route to the ALB.

- E. Create Amazon Route 53 aliases, health checks, and failover routing policies to route to the ALB.
- F. Convert the DynamoDB table to a global table.

**Answer:** CDF

**Explanation:**

C. Create new ALB and Auto Scaling group resources in the new Region and configure the new ALB to direct traffic to the new Auto Scaling group. This will allow users in the new Region to access the application with lower latency by reducing the network hops between the user and the application servers.

\* D. Create Amazon Route 53 records, health checks, and latency-based routing policies to route to the ALB. This will enable Route 53 to route user traffic to the nearest healthy ALB, based on the latency between the user and the ALBs.

\* F. Convert the DynamoDB table to a global table. This will enable reads and writes to the table in both Regions with low latency, improving the overall response time of the application

**NEW QUESTION 57**

A company has migrated its container-based applications to Amazon EKS and want to establish automated email notifications. The notifications sent to each email address are for specific activities related to EKS components. The solution will include Amazon SNS topics and an AWS Lambda function to evaluate incoming log events and publish messages to the correct SNS topic.

Which logging solution will support these requirements?

- A. Enable Amazon CloudWatch Logs to log the EKS component
- B. Create a CloudWatch subscription filter for each component with Lambda as the subscription feed destination.
- C. Enable Amazon CloudWatch Logs to log the EKS component
- D. Create CloudWatch Logs Insights queries linked to Amazon EventBridge events that invoke Lambda.
- E. Enable Amazon S3 logging for the EKS component
- F. Configure an Amazon CloudWatch subscription filter for each component with Lambda as the subscription feed destination.
- G. Enable Amazon S3 logging for the EKS component
- H. Configure S3 PUT Object event notifications with AWS Lambda as the destination.

**Answer:** A

**Explanation:**

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html#LambdaFunctionExample>

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html>

**NEW QUESTION 62**

A DevOps team is merging code revisions for an application that uses an Amazon RDS Multi-AZ DB cluster for its production database. The DevOps team uses continuous integration to periodically verify that the application works. The DevOps team needs to test the changes before the changes are deployed to the production database.

Which solution will meet these requirements?

- A. Use a buildspec file in AWS CodeBuild to restore the DB cluster from a snapshot of the production database run integration tests, and drop the restored database after verification.
- B. Deploy the application to production
- C. Configure an audit log of data control language (DCL) operations to capture database activities to perform if verification fails.
- D. Create a snapshot of the DB cluster before deploying the application Use the Update requires Replacement property on the DB instance in AWS CloudFormation to deploy the application and apply the changes.
- E. Ensure that the DB cluster is a Multi-AZ deployment
- F. Deploy the application with the update
- G. Fail over to the standby instance if verification fails.

**Answer:** A

**Explanation:**

This solution will meet the requirements because it will create a temporary copy of the production database using a snapshot, run the integration tests on the copy, and delete the copy after the tests are done. This way, the production database will not be affected by the code revisions, and the DevOps team can test the changes before deploying them to production. A buildspec file is a YAML file that contains the commands and settings that CodeBuild uses to run a build<sup>1</sup>. The buildspec file can specify the steps to restore the DB cluster from a snapshot, run the integration tests, and drop the restored database<sup>2</sup>

**NEW QUESTION 65**

A company has multiple development groups working in a single shared AWS account. The Senior Manager of the groups wants to be alerted via a third-party API call when the creation of resources approaches the service limits for the account.

Which solution will accomplish this with the LEAST amount of development effort?

- A. Create an Amazon CloudWatch Event rule that runs periodically and targets an AWS Lambda function
- B. Within the Lambda function, evaluate the current state of the AWS environment and compare deployed resource values to resource limits on the account
- C. Notify the Senior Manager if the account is approaching a service limit.
- D. Deploy an AWS Lambda function that refreshes AWS Trusted Advisor checks, and configure an Amazon CloudWatch Events rule to run the Lambda function periodically
- E. Create another CloudWatch Events rule with an event pattern matching Trusted Advisor events and a target Lambda function
- F. In the target Lambda function, notify the Senior Manager.
- G. Deploy an AWS Lambda function that refreshes AWS Personal Health Dashboard checks, and configure an Amazon CloudWatch Events rule to run the Lambda function periodically
- H. Create another CloudWatch Events rule with an event pattern matching Personal Health Dashboard events and a target Lambda function
- I. In the target Lambda function, notify the Senior Manager.
- J. Add an AWS Config custom rule that runs periodically, checks the AWS service limit status, and streams notifications to an Amazon SNS topic
- K. Deploy an AWS Lambda function that notifies the Senior Manager, and subscribe the Lambda function to the SNS topic.

**Answer:** B

**Explanation:**

To meet the requirements, the company needs to create a solution that alerts the Senior Manager when the creation of resources approaches the service limits for the account with the least amount of development effort. The company can use AWS Trusted Advisor, which is a service that provides best practice recommendations for cost optimization, performance, security, and service limits. The company can deploy an AWS Lambda function that refreshes Trusted Advisor checks, and configure an Amazon CloudWatch Events rule to run the Lambda function periodically. This will ensure that Trusted Advisor checks are up to date and reflect the current state of the account. The company can then create another CloudWatch Events rule with an event pattern matching Trusted Advisor events and a target Lambda function. The event pattern can filter for events related to service limit checks and their status. The target Lambda function can notify the Senior Manager via a third-party API call if the event indicates that the account is approaching or exceeding a service limit.

#### NEW QUESTION 70

A company's development team uses AWS CloudFormation to deploy its application resources. The team must use for any changes to the environment. The team cannot use the AWS Management Console or the AWS CLI to make manual changes directly.

The team uses a developer IAM role to access the environment. The role is configured with the AdministratorAccess managed policy. The company has created a new CloudFormationDeployment IAM role that has the following policy.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "elasticloadbalancing:*",
        "lambda:*",
        "dynamodb:*"
      ],
      "Resource": "*"
    }
  ]
}
```

The company wants to ensure that only CloudFormation can use the new role. The development team cannot make any manual changes to the deployed resources. Which combination of steps meets these requirements? (Select THREE.)

- A. Remove the AdministratorAccess policy
- B. Assign the ReadOnlyAccess managed IAM policy to the developer role
- C. Instruct the developers to use the CloudFormationDeployment role as a CloudFormation service role when the developers deploy new stacks.
- D. Update the trust of CloudFormationDeployment role to allow the developer IAM role to assume the CloudFormationDeployment role.
- E. Configure the IAM user to be able to get and pass the CloudFormationDeployment role if cloudformation actions for resources.
- F. Update the trust of the CloudFormationDeployment role to allow the cloudformation.amazonaws.com AWS principal to perform the iam:AssumeRole action
- G. Remove the AdministratorAccess policy
- H. Assign the ReadOnlyAccess managed IAM policy to the developer role. Instruct the developers to assume the CloudFormationDeployment role when they deploy new stacks
- I. Add an IAM policy to CloudFormationDeployment to allow cloudformation:\* on all resources and add a policy that allows the iam:PassRole action for ARN of CloudFormationDeployment if iam:PassedToService equals cloudformation.amazonaws.com

**Answer:** ADF

#### Explanation:

A comprehensive and detailed explanation is:

? Option A is correct because removing the AdministratorAccess policy and assigning the ReadOnlyAccess managed IAM policy to the developer role is a valid way to prevent the developers from making any manual changes to the deployed resources. The AdministratorAccess policy grants full access to all AWS resources and actions, which is not necessary for the developers. The ReadOnlyAccess policy grants read-only access to most AWS resources and actions, which is sufficient for the developers to view the status of their stacks. Instructing the developers to use the CloudFormationDeployment role as a CloudFormation service role when they deploy new stacks is also a valid way to ensure that only CloudFormation can use the new role. A CloudFormation service role is an IAM role that allows CloudFormation to make calls to resources in a stack on behalf of the user. The user can specify a service role when they create or update a stack, and CloudFormation will use that role's credentials for all operations that are performed on that stack.

? Option B is incorrect because updating the trust of CloudFormationDeployment role to allow the developer IAM role to assume the CloudFormationDeployment role is not a valid solution. This would allow the developers to manually assume the CloudFormationDeployment role and perform actions on the deployed resources, which is not what the company wants. The trust of CloudFormationDeployment role should only allow the cloudformation.amazonaws.com AWS principal to assume the role, as in option D.

? Option C is incorrect because configuring the IAM user to be able to get and pass the CloudFormationDeployment role if cloudformation actions for resources is not a valid solution. This would allow the developers to manually pass the CloudFormationDeployment role to other services or resources, which is not what the company wants. The IAM user should only be able to pass the CloudFormationDeployment role as a service role when they create or update a stack with CloudFormation, as in option A.

? Option D is correct because updating the trust of CloudFormationDeployment role to allow the cloudformation.amazonaws.com AWS principal to perform the iam:AssumeRole action is a valid solution. This allows CloudFormation to assume the CloudFormationDeployment role and access resources in other services on behalf of the user. The trust policy of an IAM role defines which entities can assume the role. By specifying cloudformation.amazonaws.com as the principal, you grant permission only to CloudFormation to assume this role.

? Option E is incorrect because instructing the developers to assume the CloudFormationDeployment role when they deploy new stacks is not a valid solution. This would allow the developers to manually assume the CloudFormationDeployment role and perform actions on the deployed resources, which is not what the company wants. The developers should only use the CloudFormationDeployment role as a service role when they deploy new stacks with CloudFormation, as in option A.

? Option F is correct because adding an IAM policy to CloudFormationDeployment that allows cloudformation:\* on all resources and adding a policy that allows the iam:PassRole action for ARN of CloudFormationDeployment if iam:PassedToService equals cloudformation.amazonaws.com are valid solutions. The first policy grants permission for CloudFormationDeployment to perform any



action with any resource using cloudformation.amazonaws.com as a service principal<sup>3</sup>. The second policy grants permission for passing this role only if it is passed by cloudformation.amazonaws.com as a service principal<sup>4</sup>. This ensures that only CloudFormation can use this role.

References:

- ? 1: AWS CloudFormation service roles
- ? 2: How to use trust policies with IAM roles
- ? 3: AWS::IAM::Policy
- ? 4: IAM: Pass an IAM role to a specific AWS service

#### NEW QUESTION 71

A company has many applications. Different teams in the company developed the applications by using multiple languages and frameworks. The applications run on premises and on different servers with different operating systems. Each team has its own release protocol and process. The company wants to reduce the complexity of the release and maintenance of these applications.

The company is migrating its technology stacks, including these applications, to AWS. The

company wants centralized control of source code, a consistent and automatic delivery pipeline, and as few maintenance tasks as possible on the underlying infrastructure.

What should a DevOps engineer do to meet these requirements?

- A. Create one AWS CodeCommit repository for all application
- B. Put each application's code in a different branch
- C. Merge the branches, and use AWS CodeBuild to build the application
- D. Use AWS CodeDeploy to deploy the applications to one centralized application server.
- E. Create one AWS CodeCommit repository for each of the application
- F. Use AWS CodeBuild to build the applications one at a time
- G. Use AWS CodeDeploy to deploy the applications to one centralized application server.
- H. Create one AWS CodeCommit repository for each of the application
- I. Use AWS CodeBuild to build the applications one at a time and to create one AMI for each server
- J. Use AWS CloudFormation StackSets to automatically provision and decommission Amazon EC2 fleets by using these AMIs.
- K. Create one AWS CodeCommit repository for each of the application
- L. Use AWS CodeBuild to build one Docker image for each application in Amazon Elastic Container Registry (Amazon ECR). Use AWS CodeDeploy to deploy the applications to Amazon Elastic Container Service (Amazon ECS) on infrastructure that AWS Fargate manages.

**Answer: D**

#### Explanation:

because of "as few maintenance tasks as possible on the underlying infrastructure". Fargate does that better than "one centralized application server"

#### NEW QUESTION 73

A company provides an application to customers. The application has an Amazon API Gateway REST API that invokes an AWS Lambda function. On initialization, the Lambda function loads a large amount of data from an Amazon DynamoDB table. The data load process results in long cold-start times of 8-10 seconds. The DynamoDB table has DynamoDB Accelerator (DAX) configured.

Customers report that the application intermittently takes a long time to respond to requests. The application receives thousands of requests throughout the day. In the middle of the day, the application experiences 10 times more requests than at any other time of the day. Near the end of the day, the application's request volume decreases to 10% of its normal total.

A DevOps engineer needs to reduce the latency of the Lambda function at all times of the day.

Which solution will meet these requirements?

- A. Configure provisioned concurrency on the Lambda function with a concurrency value of 1. Delete the DAX cluster for the DynamoDB table.
- B. Configure reserved concurrency on the Lambda function with a concurrency value of 0.
- C. Configure provisioned concurrency on the Lambda function
- D. Configure AWS Application Auto Scaling on the Lambda function with provisioned concurrency values set to a minimum of 1 and a maximum of 100.
- E. Configure reserved concurrency on the Lambda function
- F. Configure AWS Application Auto Scaling on the API Gateway API with a reserved concurrency maximum value of 100.

**Answer: C**

#### Explanation:

The following are the steps that the DevOps engineer should take to reduce the latency of the Lambda function at all times of the day:

? Configure provisioned concurrency on the Lambda function.

? Configure AWS Application Auto Scaling on the Lambda function with provisioned concurrency values set to a minimum of 1 and a maximum of 100.

The provisioned concurrency setting ensures that there is always a minimum number of Lambda function instances available to handle requests. The Application Auto Scaling setting will automatically scale the number of Lambda function instances up or down based on the demand for the application.

This solution will ensure that the Lambda function is able to handle the increased load during the middle of the day, while also keeping the cold-start latency low.

The following are the reasons why the other options are not correct:

? Option A is incorrect because it will not reduce the cold-start latency of the Lambda function.

? Option B is incorrect because it will not scale the number of Lambda function instances up or down based on demand.

? Option D is incorrect because it will only configure reserved concurrency on the API Gateway API, which will not affect the Lambda function.

#### NEW QUESTION 78

A company has 20 service teams. Each service team is responsible for its own microservice. Each service team uses a separate AWS account for its microservice and a VPC with the 192.168.0.0/22 CIDR block. The company manages the AWS accounts with AWS Organizations.

Each service team hosts its microservice on multiple Amazon EC2 instances behind an Application Load Balancer. The microservices communicate with each other across the public internet. The company's security team has issued a new guideline that all communication between microservices must use HTTPS over private network connections and cannot traverse the public internet.

A DevOps engineer must implement a solution that fulfills these obligations and minimizes the number of changes for each service team.

Which solution will meet these requirements?

- A. Create a new AWS account in AWS Organizations. Create a VPC in this account and use AWS Resource Access Manager to share the private subnets of this VPC with the organization. Instruct the service teams to launch a new
- B. Network Load Balancer (NLB) and EC2 instances that use the shared private subnets. Use the NLB DNS names for communication between microservices.
- C. Create a Network Load Balancer (NLB) in each of the microservice VPCs. Use AWS PrivateLink to create VPC endpoints in each AWS account for the NLBs.

Create subscriptions to each VPC endpoint in each of the other AWS accounts Use the VPC endpoint DNS names for communication between microservices.  
D. Create a Network Load Balancer (NLB) in each of the microservice VPCs Create VPC peering connections between each of the microservice VPCs Update the route tables for each VPC to use the peering links Use the NLB DNS names for communication between microservices.  
E. Create a new AWS account in AWS Organizations Create a transit gateway in this account and use AWS Resource Access Manager to share the transit gateway with the organizatio  
F. In each of the microservice VPC  
G. create a transit gateway attachment to the shared transit gateway Update the route tables of each VPC to use the transit gateway Create a Network Load Balancer (NLB) in each of the microservice VPCs Use the NLB DNS names for communication between microservices.

**Answer: B**

**Explanation:**

<https://aws.amazon.com/blogs/networking-and-content-delivery/connecting-networks-with-overlapping-ip-ranges/> Private link is the best option because Transit Gateway doesn't support overlapping CIDR ranges.

**NEW QUESTION 82**

A media company has several thousand Amazon EC2 instances in an AWS account. The company is using Slack and a shared email inbox for team communications and important updates. A DevOps engineer needs to send all AWS-scheduled EC2 maintenance notifications to the Slack channel and the shared inbox. The solution must include the instances' Name and Owner tags. Which solution will meet these requirements?

- A. Integrate AWS Trusted Advisor with AWS Config Configure a custom AWS Config rule to invoke an AWS Lambda function to publish notifications to an Amazon Simple Notification Service (Amazon SNS) topic Subscribe a Slack channel endpoint and the shared inbox to the topic.
- B. Use Amazon EventBridge to monitor for AWS Health Events Configure the maintenance events to target an Amazon Simple Notification Service (Amazon SNS) topic Subscribe an AWS Lambda function to the SNS topic to send notifications to the Slack channel and the shared inbox.
- C. Create an AWS Lambda function that sends EC2 maintenance notifications to the Slack channel and the shared inbox Monitor EC2 health events by using Amazon CloudWatch metrics Configure a CloudWatch alarm that invokes the Lambda function when a maintenance notification is received.
- D. Configure AWS Support integration with AWS CloudTrail Create a CloudTrail lookup event to invoke an AWS Lambda function to pass EC2 maintenance notifications to Amazon Simple Notification Service (Amazon SNS) Configure Amazon SNS to target the Slack channel and the shared inbox.

**Answer: B**

**Explanation:**

<https://docs.aws.amazon.com/health/latest/ug/cloudwatch-events-health.html>

**NEW QUESTION 83**

A company requires its developers to tag all Amazon Elastic Block Store (Amazon EBS) volumes in an account to indicate a desired backup frequency. This requirement Includes EBS volumes that do not require backups. The company uses custom tags named Backup\_Frequency that have values of none, dally, or weekly that correspond to the desired backup frequency. An audit finds that developers are occasionally not tagging the EBS volumes. A DevOps engineer needs to ensure that all EBS volumes always have the Backup\_Frequency tag so that the company can perform backups at least weekly unless a different value is specified. Which solution will meet these requirements?

- A. Set up AWS Config in the accoun
- B. Create a custom rule that returns a compliance failure for all Amazon EC2 resources that do not have a Backup Frequency tag applied. Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly.
- C. Set up AWS Config in the accoun
- D. Use a managed rule that returns a compliance failure for EC2::Volume resources that do not have a Backup Frequency tag applie
- E. Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly.
- F. Turn on AWS CloudTrail in the accoun
- G. Create an Amazon EventBridge rule that reacts to EBS CreateVolume event
- H. Configure a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekl
- I. Specify the runbook as the target of the rule.
- J. Turn on AWS CloudTrail in the accoun
- K. Create an Amazon EventBridge rule that reacts to EBS CreateVolume events or EBS ModifyVolume event
- L. Configure a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekl
- M. Specify the runbook as the target of the rule.

**Answer: B**

**Explanation:**

The following are the steps that the DevOps engineer should take to ensure that all EBS volumes always have the Backup\_Frequency tag so that the company can perform backups at least weekly unless a different value is specified:

? Set up AWS Config in the account.

? Use a managed rule that returns a compliance failure for EC2::Volume resources that do not have a Backup Frequency tag applied.

? Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly.

The managed rule AWS::Config::EBSVolumesWithoutBackupTag will return a compliance failure for any EBS volume that does not have the Backup\_Frequency tag applied. The remediation action will then use the Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly to the EBS volume.

**NEW QUESTION 86**

A company is running an application on Amazon EC2 instances in an Auto Scaling group. Recently an issue occurred that prevented EC2 instances from launching successfully and it took several hours for the support team to discover the issue. The support team wants to be notified by email whenever an EC2 instance does not start successfully. Which action will accomplish this?

- A. Add a health check to the Auto Scaling group to invoke an AWS Lambda function whenever an instance status is impaired.
- B. Configure the Auto Scaling group to send a notification to an Amazon SNS topic whenever a failed instance launch occurs.
- C. Create an Amazon CloudWatch alarm that invokes an AWS Lambda function when a failed Attachinstances Auto Scaling API call is made.
- D. Create a status check alarm on Amazon EC2 to send a notification to an Amazon SNS topic whenever a status check fail occurs.

**Answer:** B

**Explanation:**

<https://docs.aws.amazon.com/autoscaling/ec2/userguide/ASGettingNotifications.html#auto-scaling-sns-notifications>

#### NEW QUESTION 88

An IT team has built an AWS CloudFormation template so others in the company can quickly and reliably deploy and terminate an application. The template creates an Amazon EC2 instance with a user data script to install the application and an Amazon S3 bucket that the application uses to serve static webpages while it is running.

All resources should be removed when the CloudFormation stack is deleted. However, the team observes that CloudFormation reports an error during stack deletion, and the S3 bucket created by the stack is not deleted.

How can the team resolve the error in the MOST efficient manner to ensure that all resources are deleted without errors?

- A. Add a DeletionPolicy attribute to the S3 bucket resource, with the value Delete forcing the bucket to be removed when the stack is deleted.
- B. Add a custom resource with an AWS Lambda function with the DependsOn attribute specifying the S3 bucket, and an IAM role.
- C. Write the Lambda function to delete all objects from the bucket when RequestType is Delete.
- D. Identify the resource that was not deleted.
- E. Manually empty the S3 bucket and then delete it.
- F. Replace the EC2 and S3 bucket resources with a single AWS OpsWorks Stacks resource.
- G. Define a custom recipe for the stack to create and delete the EC2 instance and the S3 bucket.

**Answer:** B

**Explanation:**

<https://aws.amazon.com/premiumsupport/knowledge-center/cloudformation-s3-custom-resources/>

#### NEW QUESTION 91

A company's security policies require the use of security hardened AMIs in production environments. A DevOps engineer has used EC2 Image Builder to create a pipeline that builds the AMIs on a recurring schedule.

The DevOps engineer needs to update the launch templates of the company's Auto Scaling groups. The Auto Scaling groups must use the newest AMIs during the launch of Amazon EC2 instances.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Configure an Amazon EventBridge rule to receive new AMI events from Image Builder.
- B. Target an AWS Systems Manager Run Command document that updates the launch templates of the Auto Scaling groups with the newest AMI ID.
- C. Configure an Amazon EventBridge rule to receive new AMI events from Image Builder.
- D. Target an AWS Lambda function that updates the launch templates of the Auto Scaling groups with the newest AMI ID.
- E. Configure the launch template to use a value from AWS Systems Manager Parameter Store for the AMI ID.
- F. Configure the Image Builder pipeline to update the Parameter Store value with the newest AMI ID.
- G. Configure the Image Builder distribution settings to update the launch templates with the newest AMI ID.
- H. Configure the Auto Scaling groups to use the newest version of the launch template.

**Answer:** C

**Explanation:**

? The most operationally efficient solution is to use AWS Systems Manager Parameter Store<sup>1</sup> to store the AMI ID and reference it in the launch template<sup>2</sup>. This way, the launch template does not need to be updated every time a new AMI is created by Image Builder. Instead, the Image Builder pipeline can update the Parameter Store value with the newest AMI ID<sup>3</sup>, and the Auto Scaling group can launch instances using the latest value from Parameter Store.

? The other solutions require updating the launch template or creating a new version of it every time a new AMI is created, which adds complexity and overhead. Additionally, using EventBridge rules and Lambda functions or Run Command documents introduces additional dependencies and potential points of failure.

References: 1: AWS Systems Manager Parameter Store 2: Using AWS Systems Manager parameters instead of AMI IDs in launch templates 3: Update an SSM parameter with Image Builder

#### NEW QUESTION 94

A security review has identified that an AWS CodeBuild project is downloading a database population script from an Amazon S3 bucket using an unauthenticated request. The security team does not allow unauthenticated requests to S3 buckets for this project.

How can this issue be corrected in the MOST secure manner?

- A. Add the bucket name to the AllowedBuckets section of the CodeBuild project setting.
- B. Update the build spec to use the AWS CLI to download the database population script.
- C. Modify the S3 bucket settings to enable HTTPS basic authentication and specify a token.
- D. Update the build spec to use cURL to pass the token and download the database population script.
- E. Remove unauthenticated access from the S3 bucket with a bucket policy.
- F. Modify the service role for the CodeBuild project to include Amazon S3 access.
- G. Use the AWS CLI to download the database population script.
- H. Remove unauthenticated access from the S3 bucket with a bucket policy.
- I. Use the AWS CLI to download the database population script using an IAM access key and a secret access key.

**Answer:** C

**Explanation:**

A bucket policy is a resource-based policy that defines who can access a specific S3 bucket and what actions they can perform on it. By removing unauthenticated access from the bucket policy, you can prevent anyone without valid credentials from accessing the bucket. A service role is an IAM role that allows an AWS service, such as CodeBuild, to perform actions on your behalf. By modifying the service role for the CodeBuild project to include Amazon S3 access, you can grant the project permission to read and write objects in the S3 bucket. The AWS CLI is a command-line tool that allows you to interact with AWS services, such as S3, using commands in your terminal. By using the AWS CLI to download the database population script, you can leverage the service role credentials and encryption to secure the data transfer.

For more information, you can refer to these web pages:

? [Using bucket policies and user policies - Amazon Simple Storage Service]



? [Create a service role for CodeBuild - AWS CodeBuild]  
 ? [AWS Command Line Interface]

#### NEW QUESTION 98

A DevOps engineer is working on a project that is hosted on Amazon Linux and has failed a security review. The DevOps manager has been asked to review the company buildspec.yaml file for an AWS CodeBuild project and provide recommendations. The buildspec. yaml file is configured as follows:

```
env:
  variables:
    AWS_ACCESS_KEY_ID: AKIAJF7BRFWJBA4GHXNA
    AWS_SECRET_ACCESS_KEY: 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
    AWS_DEFAULT_REGION: us-east-1
    DB_PASSWORD: cuj5RptFa3va
phases:
  build:
    commands:
      - aws s3 cp s3://db-deploy-bucket/my.cnf.template /tmp/my.cnf
      - sed -i 's/DB_PW/${DB_PASSWORD}/' /tmp/my.cnf
      - aws s3 cp s3://db-deploy-bucket/instance.key /tmp/instance.key
      - chmod 600 /tmp/instance.key
      - scp -i /tmp/instance.key /tmp/my.cnf root@10.25.15.23:/etc/my.cnf
      - ssh -i /tmp/instance.key root@10.25.15.23 /etc/init.d/mysqld restart
```

What changes should be recommended to comply with AWS security best practices? (Select THREE.)

- A. Add a post-build command to remove the temporary files from the container before termination to ensure they cannot be seen by other CodeBuild users.
- B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable.
- C. Store the db\_password as a SecureString value in AWS Systems Manager Parameter Store and then remove the db\_password from the environment variables.
- D. Move the environment variables to the 'db.-deploy-bucket' Amazon S3 bucket, add a prebuild stage to download then export the variables.
- E. Use AWS Systems Manager run command versus sec and ssh commands directly to the instance.

**Answer:** BCE

#### Explanation:

B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable. C. Store the DB\_PASSWORD as a SecureString value in AWS Systems Manager Parameter Store and then remove the DB\_PASSWORD from the environment variables. E. Use AWS Systems Manager run command versus scp and ssh commands directly to the instance.

#### NEW QUESTION 99

A company deploys updates to its Amazon API Gateway API several times a week by using an AWS CodePipeline pipeline. As part of the update process the company exports the JavaScript SDK for the API from the API. Gateway console and uploads the SDK to an Amazon S3 bucket. The company has configured an Amazon CloudFront distribution that uses the S3 bucket as an origin. Web client then download the SDK by using the CloudFront distribution's endpoint. A DevOps engineer needs to implement a solution to make the new SDK available automatically during new API deployments. Which solution will meet these requirements?

- A. Create a CodePipeline action immediately after the deployment stage of the AP
- B. Configure the action to invoke an AWS Lambda function
- C. Configure the Lambda function to download the SDK from API Gateway, upload the SDK to the S3 bucket and create a CloudFront invalidation for the SDK path.
- D. Create a CodePipeline action immediately after the deployment stage of the API. Configure the action to use the CodePipeline integration with AP
- E. Gateway to export the SDK to Amazon S3. Create another action that uses the CodePipeline integration with Amazon S3 to invalidate the cache for the SDK path.
- F. Create an Amazon EventBridge rule that reacts to UpdateStage events from aws apigateway. Configure the rule to invoke an AWS Lambda function to download the SDK from API Gateway, upload the SDK to the S3 bucket and call the CloudFront API to create an invalidation for the SDK path.
- G. Create an Amazon EventBridge rule that reacts to Create
- H. Deployment events from aws apigatewa
- I. Configure the rule to invoke an AWS Lambda function to download the SDK from AP
- J. Gateway upload the SDK to the S3 bucket and call the S3 API to invalidate the cache for the SDK path.

**Answer:** A

#### Explanation:

This solution would allow the company to automate the process of updating the SDK and making it available to web clients. By adding a CodePipeline action immediately after the deployment stage of the API, the Lambda function will be invoked automatically each time the API is updated. The Lambda function should be able to download the new SDK from API Gateway, upload it to the S3 bucket and also create a CloudFront invalidation for the SDK path so that the latest version of the SDK is available for the web clients. This is the most straight forward solution and it will meet the requirements.

#### NEW QUESTION 103

A company has an application that is using a MySQL-compatible Amazon Aurora Multi-AZ DB cluster as the database. A cross-Region read replica has been created for disaster recovery purposes. A DevOps engineer wants to automate the promotion of the replica so it becomes the primary database instance in the event of a failure.

Which solution will accomplish this?

- A. Configure a latency-based Amazon Route 53 CNAME with health checks so it points to both the primary and replica endpoint
- B. Subscribe an Amazon SNS topic to Amazon RDS failure notifications from AWS CloudTrail and use that topic to invoke an AWS Lambda function that will promote the replica instance as the primary.
- C. Create an Aurora custom endpoint to point to the primary database instance
- D. Configure the application to use this endpoint
- E. Configure AWS CloudTrail to run an AWS Lambda function to promote the replica instance and modify the custom endpoint to point to the newly promoted instance.

- F. Create an AWS Lambda function to modify the application's AWS CloudFormation template to promote the replica, apply the template to update the stack, and point the application to the newly promoted instance.
- G. Create an Amazon CloudWatch alarm to invoke this Lambda function after the failure event occurs.
- H. Store the Aurora endpoint in AWS Systems Manager Parameter Store.
- I. Create an Amazon EventBridge event that detects the database failure and runs an AWS Lambda function to promote the replica instance and update the endpoint URL stored in AWS Systems Manager Parameter Store.
- J. Code the application to reload the endpoint from Parameter Store if a database connection fails.

**Answer: D**

**Explanation:**

EventBridge is needed to detect the database failure. Lambda is needed to promote the replica as it's in another Region (manual promotion, otherwise). Storing and updating the endpoint in Parameter store is important in updating the application. Look at High Availability section of Aurora FAQ:  
<https://aws.amazon.com/rds/aurora/faqs/>

**NEW QUESTION 106**

To run an application, a DevOps engineer launches an Amazon EC2 instance with public IP addresses in a public subnet. A user data script obtains the application artifacts and installs them on the instances upon launch. A change to the security classification of the application now requires the instances to run with no access to the internet. While the instances launch successfully and show as healthy, the application does not seem to be installed. Which of the following should successfully install the application while complying with the new rule?

- A. Launch the instances in a public subnet with Elastic IP addresses attached.
- B. Once the application is installed and running, run a script to disassociate the Elastic IP addresses afterwards.
- C. Set up a NAT gateway.
- D. Deploy the EC2 instances to a private subnet.
- E. Update the private subnet's route table to use the NAT gateway as the default route.
- F. Publish the application artifacts to an Amazon S3 bucket and create a VPC endpoint for S3. Assign an IAM instance profile to the EC2 instances so they can read the application artifacts from the S3 bucket.
- G. Create a security group for the application instances and allow only outbound traffic to the artifact repository.
- H. Remove the security group rule once the install is complete.

**Answer: C**

**Explanation:**

EC2 instances running in private subnets of a VPC can now have controlled access to S3 buckets, objects, and API functions that are in the same region as the VPC. You can use an S3 bucket policy to indicate which VPCs and which VPC Endpoints have access to your S3 buckets 1-  
<https://aws.amazon.com/pt/blogs/aws/new-vpc-endpoint-for-amazon-s3/>

**NEW QUESTION 107**

A DevOps engineer is working on a data archival project that requires the migration of on-premises data to an Amazon S3 bucket. The DevOps engineer develops a script that incrementally archives on-premises data that is older than 1 month to Amazon S3. Data that is transferred to Amazon S3 is deleted from the on-premises location. The script uses the S3 PutObject operation.

During a code review the DevOps engineer notices that the script does not verify whether the data was successfully copied to Amazon S3. The DevOps engineer must update the script to ensure that data is not corrupted during transmission. The script must use MD5 checksums to verify data integrity before the on-premises data is deleted.

Which solutions for the script will meet these requirements? (Select TWO.)

- A. Check the returned response for the Versioned Compare the returned Versioned against the MD5 checksum.
- B. Include the MD5 checksum within the Content-MD5 parameter.
- C. Check the operation's return status to find out if an error was returned.
- D. Include the checksum digest within the tagging parameter as a URL query parameter.
- E. Check the returned response for the ETag.
- F. Compare the returned ETag against the MD5 checksum.
- G. Include the checksum digest within the Metadata parameter as a name-value pair. After upload use the S3 HeadObject operation to retrieve metadata from the object.

**Answer: BD**

**Explanation:**

<https://docs.aws.amazon.com/AmazonS3/latest/userguide/checking-object-integrity.html>

**NEW QUESTION 110**

A company that runs many workloads on AWS has an Amazon EBS spend that has increased over time. The DevOps team notices there are many unattached EBS volumes. Although there are workloads where volumes are detached, volumes over 14 days old are stale and no longer needed. A DevOps engineer has been tasked with creating automation that deletes unattached EBS volumes that have been unattached for 14 days.

Which solution will accomplish this?

- A. Configure the AWS Config ec2-volume-in-use-check managed rule with a configuration changes trigger type and an Amazon EC2 volume resource target.
- B. Create a new Amazon CloudWatch Events rule scheduled to execute an AWS Lambda function in 14 days to delete the specified EBS volume.
- C. Use Amazon EC2 and Amazon Data Lifecycle Manager to configure a volume lifecycle policy.
- D. Set the interval period for unattached EBS volumes to 14 days and set the retention rule to delete.
- E. Set the policy target volumes as \*.
- F. Create an Amazon CloudWatch Events rule to execute an AWS Lambda function daily.
- G. The Lambda function should find unattached EBS volumes and tag them with the current date, and delete unattached volumes that have tags with dates that are more than 14 days old.
- H. Use AWS Trusted Advisor to detect EBS volumes that have been detached for more than 14 days.
- I. Execute an AWS Lambda function that creates a snapshot and then deletes the EBS volume.

**Answer: C**

**Explanation:**

The requirement is to create automation that deletes unattached EBS volumes that have been unattached for 14 days. To do this, the DevOps engineer needs to use the following steps:

? Create an Amazon CloudWatch Events rule to execute an AWS Lambda function

daily. CloudWatch Events is a service that enables event-driven architectures by delivering events from various sources to targets. Lambda is a service that lets you

run code without provisioning or managing servers. By creating a CloudWatch Events rule that executes a Lambda function daily, the DevOps engineer can schedule a recurring task to check and delete unattached EBS volumes.

? The Lambda function should find unattached EBS volumes and tag them with the

current date, and delete unattached volumes that have tags with dates that are more than 14 days old. The Lambda function can use the EC2 API to list and filter unattached EBS volumes based on their state and tags. The function can then tag each unattached volume with the current date using the create-tags command.

The function can also compare the tag value with the current date and delete any unattached volume that has been tagged more than 14 days ago using the delete-volume command.

**NEW QUESTION 111**

A company wants to deploy a workload on several hundred Amazon EC2 instances. The company will provision the EC2 instances in an Auto Scaling group by using a launch template.

The workload will pull files from an Amazon S3 bucket, process the data, and put the results into a different S3 bucket. The EC2 instances must have least-privilege permissions and must use temporary security credentials.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Create an IAM role that has the appropriate permissions for S3 bucket
- B. Add the IAM role to an instance profile.
- C. Update the launch template to include the IAM instance profile.
- D. Create an IAM user that has the appropriate permissions for Amazon S3. Generate a secret key and token.
- E. Create a trust anchor and profile
- F. Attach the IAM role to the profile.
- G. Update the launch template
- H. Modify the user data to use the new secret key and token.

**Answer:** AB

**Explanation:**

To meet the requirements of deploying a workload on several hundred EC2 instances with least-privilege permissions and temporary security credentials, the company should use an IAM role and an instance profile. An IAM role is a way to grant permissions to an entity that you trust, such as an EC2 instance. An instance profile is a container for an IAM role that you can use to pass role information to an EC2 instance when the instance starts. By using an IAM role and an instance profile, the EC2 instances can automatically receive temporary security credentials from the AWS Security Token Service (STS) and use them to access the S3 buckets. This way, the company does not need to manage or rotate any long-term credentials, such as IAM users or access keys.

To use an IAM role and an instance profile, the company should create an IAM role that has the appropriate permissions for S3 buckets. The permissions should allow the EC2 instances to read from the source S3 bucket and write to the destination S3 bucket. The company should also create a trust policy for the IAM role that specifies that EC2 is allowed to assume the role. Then, the company should add the IAM role to an instance profile. An instance profile can have only one IAM role, so the company does not need to create multiple roles or profiles for this scenario.

Next, the company should update the launch template to include the IAM instance profile. A launch template is a way to save launch parameters for EC2 instances, such as the instance type, security group, user data, and IAM instance profile. By using a launch template, the company can ensure that all EC2 instances in the Auto Scaling group have consistent configuration and permissions. The company should specify the name or ARN of the IAM instance profile in the launch template. This way, when the Auto Scaling group launches new EC2 instances based on the launch template, they will automatically receive the IAM role and its permissions through the instance profile.

The other options are not correct because they do not meet the requirements or follow best practices. Creating an IAM user and generating a secret key and token is not a good option because it involves managing long-term credentials that need to be rotated regularly. Moreover, embedding credentials in user data is not secure because user data is visible to anyone who can describe the EC2 instance. Creating a trust anchor and profile is not a valid option because trust anchors are used for certificate-based authentication, not for IAM roles or instance profiles. Modifying user data to use a new secret key and token is also not a good option because it requires updating user data every time the credentials change, which is not scalable or efficient.

References:

? 1: AWS Certified DevOps Engineer - Professional Certification | AWS Certification

| AWS

? 2: DevOps Resources - Amazon Web Services (AWS)

? 3: Exam Readiness: AWS Certified DevOps Engineer - Professional

? : IAM Roles for Amazon EC2 - AWS Identity and Access Management

? : Working with Instance Profiles - AWS Identity and Access Management

? : Launching an Instance Using a Launch Template - Amazon Elastic Compute Cloud

? : Temporary Security Credentials - AWS Identity and Access Management

**NEW QUESTION 116**

A company needs to ensure that flow logs remain configured for all existing and new VPCs in its AWS account. The company uses an AWS CloudFormation stack to manage its VPCs. The company needs a solution that will work for any VPCs that any IAM user creates.

Which solution will meet these requirements?

- A. Add the resource to the CloudFormation stack that creates the VPCs.
- B. Create an organization in AWS Organization
- C. Add the company's AWS account to the organization
- D. Create an SCP to prevent users from modifying VPC flow logs.
- E. Turn on AWS Config
- F. Create an AWS Config rule to check whether VPC flow logs are turned on
- G. Configure automatic remediation to turn on VPC flow logs.
- H. Create an IAM policy to deny the use of API calls for VPC flow log
- I. Attach the IAM policy to all IAM users.

**Answer:** C

**Explanation:**



To meet the requirements of ensuring that flow logs remain configured for all existing and new VPCs in the AWS account, the company should use AWS Config and automatic remediation. AWS Config is a service that enables customers to assess, audit, and evaluate the configurations of their AWS resources. AWS Config continuously monitors and records the configuration changes of the AWS resources and evaluates them against desired configurations. Customers can use AWS Config rules to define the desired configuration state of their AWS resources and trigger actions when a resource configuration violates a rule.

One of the AWS Config rules that customers can use is vpc-flow-logs-enabled, which checks whether VPC flow logs are enabled for all VPCs in an AWS account. Customers can also configure automatic remediation for this rule, which means that AWS Config will automatically enable VPC flow logs for any VPCs that do not have them enabled. Customers can specify the destination (CloudWatch Logs or S3) and the traffic type (all, accept, or reject) for the flow logs as remediation parameters. By using AWS Config and automatic remediation, the company can ensure that flow logs remain configured for all existing and new VPCs in its AWS account, regardless of who creates them or how they are created.

The other options are not correct because they do not meet the requirements or follow best practices. Adding the resource to the CloudFormation stack that creates the VPCs is not a sufficient solution because it will only work for VPCs that are created by using the CloudFormation stack. It will not work for VPCs that are created by using other methods, such as the console or the API. Creating an organization in AWS Organizations and creating an SCP to prevent users from modifying VPC flow logs is not a good solution because it will not ensure that flow logs are enabled for all VPCs in the first place. It will only prevent users from disabling or changing flow logs after they are enabled. Creating an IAM policy to deny the use of API calls for VPC flow logs and attaching it to all IAM users is not a valid solution because it will prevent users from enabling or disabling flow logs at all.

It will also not work for VPCs that are created by using other methods, such as the console or CloudFormation.

References:

? 1: AWS::EC2::FlowLog - AWS CloudFormation

? 2: Amazon VPC Flow Logs extends CloudFormation Support to custom format subscriptions, 1-minute aggregation intervals and tagging

? 3: Logging IP traffic using VPC Flow Logs - Amazon Virtual Private Cloud

? : About AWS Config - AWS Config

? : vpc-flow-logs-enabled - AWS Config

? : Remediate Noncompliant Resources with AWS Config Rules - AWS Config

### NEW QUESTION 117

A company has a guideline that every Amazon EC2 instance must be launched from an AMI that the company's security team produces Every month the security team sends an email message with the latest approved AMIs to all the development teams.

The development teams use AWS CloudFormation to deploy their applications. When developers launch a new service they have to search their email for the latest AMIs that the security department sent. A DevOps engineer wants to automate the process that the security team uses to provide the AMI IDs to the development teams.

What is the MOST scalable solution that meets these requirements?

- A. Direct the security team to use CloudFormation to create new versions of the AMIs and to list! the AMI ARNs in an encrypted Amazon S3 object as part of the stack's Outputs Section Instruct the developers to use a cross-stack reference to load the encrypted S3 object and obtain the most recent AMI ARNs.
- B. Direct the security team to use a CloudFormation stack to create an AWS CodePipeline pipeline that builds new AMIs and places the latest AMI ARNs in an encrypted Amazon S3 object as part of the pipeline output Instruct the developers to use a cross-stack reference within their own CloudFormation template to obtain the S3 object location and the most recent AMI ARNs.
- C. Direct the security team to use Amazon EC2 Image Builder to create new AMIs and to place the AMI ARNs as parameters in AWS Systems Manager Parameter Store Instruct the developers to specify a parameter of type SSM in their CloudFormation stack to obtain the most recent AMI ARNs from Parameter Store.
- D. Direct the security team to use Amazon EC2 Image Builder to create new AMIs and to create an Amazon Simple Notification Service (Amazon SNS) topic so that every development team can receive notification
- E. When the development teams receive a notification instruct them to write an AWS Lambda function that will update their CloudFormation stack with the most recent AMI ARNs.

**Answer: C**

**Explanation:**

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/dynamic-references.html>

### NEW QUESTION 118

A DevOps engineer is building a continuous deployment pipeline for a serverless application that uses AWS Lambda functions. The company wants to reduce the customer impact of an unsuccessful deployment. The company also wants to monitor for issues.

Which deploy stage configuration will meet these requirements?

- A. Use an AWS Serverless Application Model (AWS SAM) template to define the serverless applicatio
- B. Use AWS CodeDeploy to deploy the Lambda functions with the Canary10Percent15Minutes Deployment Preference Typ
- C. Use Amazon CloudWatch alarms to monitor the health of the functions.
- D. Use AWS CloudFormation to publish a new stack update, and include Amazon CloudWatch alarms on all resource
- E. Set up an AWS CodePipeline approval action for a developer to verify and approve the AWS CloudFormation change set.
- F. Use AWS CloudFormation to publish a new version on every stack update, and include Amazon CloudWatch alarms on all resource
- G. Use the RoutingConfig property of the AWS::Lambda::Alias resource to update the traffic routing during the stack update.
- H. Use AWS CodeBuild to add sample event payloads for testing to the Lambda function
- I. Publish a new version of the functions, and include Amazon CloudWatch alarm
- J. Update the production alias to point to the new versio
- K. Configure rollbacks to occur when an alarm is in the ALARM state.

**Answer: D**

**Explanation:**

Use routing configuration on an alias to send a portion of traffic to a second function version. For example, you can reduce the risk of deploying a new version by configuring the alias to send most of the traffic to the existing version, and only a small percentage of traffic to the new version.

<https://docs.aws.amazon.com/lambda/latest/dg/configuration-aliases.html>

The following are the steps involved in the deploy stage configuration that will meet the requirements:

? Use AWS CodeBuild to add sample event payloads for testing to the Lambda functions.

? Publish a new version of the functions, and include Amazon CloudWatch alarms.

? Update the production alias to point to the new version.

? Configure rollbacks to occur when an alarm is in the ALARM state.

This configuration will help to reduce the customer impact of an unsuccessful deployment

by deploying the new version of the functions to a staging environment first. This will allow the DevOps engineer to test the new version of the functions before

deploying it to production.

The configuration will also help to monitor for issues by including Amazon CloudWatch alarms. These alarms will alert the DevOps engineer if there are any problems with the new version of the functions.

#### NEW QUESTION 122

A company is deploying a new application that uses Amazon EC2 instances. The company needs a solution to query application logs and AWS account API activity. Which solution will meet these requirements?

- A. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon CloudWatch Logs. Configure AWS CloudTrail to deliver the API logs to Amazon S3. Use CloudWatch to query both sets of logs.
- B. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon CloudWatch Logs. Configure AWS CloudTrail to deliver the API logs to CloudWatch Logs. Use CloudWatch Logs Insights to query both sets of logs.
- C. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon Kinesis. Configure AWS CloudTrail to deliver the API logs to Kinesis. Use Kinesis to load the data into Amazon Redshift. Use Amazon Redshift to query both sets of logs.
- D. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon S3. Use AWS CloudTrail to deliver the API logs to Amazon S3. Use Amazon Athena to query both sets of logs in Amazon S3.

**Answer:** D

#### Explanation:

This solution will meet the requirements because it will use Amazon S3 as a common data lake for both the application logs and the API logs. Amazon S3 is a service that provides scalable, durable, and secure object storage for any type of data. You can use the Amazon CloudWatch agent to send logs from your EC2 instances to S3 buckets, and use AWS CloudTrail to deliver the API logs to S3 buckets as well. You can also use Amazon Athena to query both sets of logs in S3 using standard SQL, without loading or transforming them. Athena is a serverless interactive query service that allows you to analyze data in S3 using a variety of data formats, such as JSON, CSV, Parquet, and ORC.

#### NEW QUESTION 126

A company hosts a security auditing application in an AWS account. The auditing application uses an IAM role to access other AWS accounts. All the accounts are in the same organization in AWS Organizations.

A recent security audit revealed that users in the audited AWS accounts could modify or delete the auditing application's IAM role. The company needs to prevent any modification to the auditing application's IAM role by any entity other than a trusted administrator IAM role. Which solution will meet these requirements?

- A. Create an SCP that includes a Deny statement for changes to the auditing application's IAM role.
- B. Include a condition that allows the trusted administrator IAM role to make change.
- C. Attach the SCP to the root of the organization.
- D. Create an SCP that includes an Allow statement for changes to the auditing application's IAM role by the trusted administrator IAM role.
- E. Include a Deny statement for changes by all other IAM principals.
- F. Attach the SCP to the IAM service in each AWS account where the auditing application has an IAM role.
- G. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM role.
- H. Include a condition that allows the trusted administrator IAM role to make change.
- I. Attach the permissions boundary to the audited AWS accounts.
- J. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM role.
- K. Include a condition that allows the trusted administrator IAM role to make change.
- L. Attach the permissions boundary to the auditing application's IAM role in the AWS accounts.

**Answer:** A

#### Explanation:

[https://docs.aws.amazon.com/organizations/latest/userguide/orgs\\_manage\\_policies\\_scps.html?icmpid=docs\\_orgs\\_console](https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_policies_scps.html?icmpid=docs_orgs_console)  
SCPs (Service Control Policies) are the best way to restrict permissions at the organizational level, which in this case would be used to restrict modifications to the IAM role used by the auditing application, while still allowing trusted administrators to make changes to it. Options C and D are not as effective because IAM permission boundaries are applied to IAM entities (users, groups, and roles), not the account itself, and must be applied to all IAM entities in the account.

#### NEW QUESTION 127

A rapidly growing company wants to scale for developer demand for AWS development environments. Development environments are created manually in the AWS Management Console. The networking team uses AWS CloudFormation to manage the networking infrastructure, exporting stack output values for the Amazon VPC and all subnets. The development environments have common standards, such as Application Load Balancers, Amazon EC2 Auto Scaling groups, security groups, and Amazon DynamoDB tables.

To keep up with demand, the DevOps engineer wants to automate the creation of development environments. Because the infrastructure required to support the application is expected to grow, there must be a way to easily update the deployed infrastructure. CloudFormation will be used to create a template for the development environments.

Which approach will meet these requirements and quickly provide consistent AWS environments for developers?

- A. Use `Fn::ImportValue` intrinsic functions in the Resources section of the template to retrieve Virtual Private Cloud (VPC) and subnet values.
- B. Use CloudFormation StackSets for the development environments, using the Count input parameter to indicate the number of environments needed.
- C. Use the `UpdateStackSet` command to update existing development environments.
- D. Use nested stacks to define common infrastructure components.
- E. To access the exported values, use `TemplateURL` to reference the networking team's template.
- F. To retrieve Virtual Private Cloud (VPC) and subnet values, use `Fn::ImportValue` intrinsic functions in the Parameters section of the root template.
- G. Use the `CreateChangeSet` and `ExecuteChangeSet` commands to update existing development environments.
- H. Use nested stacks to define common infrastructure components.
- I. Use `Fn::ImportValue` intrinsic functions with the resources of the nested stack to retrieve Virtual Private Cloud (VPC) and subnet values.
- J. Use the `CreateChangeSet` and `ExecuteChangeSet` commands to update existing development environments.
- K. Use `Fn::ImportValue` intrinsic functions in the Parameters section of the root template to retrieve Virtual Private Cloud (VPC) and subnet values.
- L. Define the development resources in the order they need to be created in the CloudFormation nested stack.
- M. Use the `CreateChangeSet`
- N. and `ExecuteChangeSet` commands to update existing development environments.

**Answer:** C

#### Explanation:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference-importvalue.html>  
<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference-importvalue.html> CF of network exports the VPC, subnet or needed information CF of application imports the above information to its stack and UpdateChangeSet/ ExecuteChangeSet

#### NEW QUESTION 132

A company uses an organization in AWS Organizations that has all features enabled. The company uses AWS Backup in a primary account and uses an AWS Key Management Service (AWS KMS) key to encrypt the backups. The company needs to automate a cross-account backup of the resources that AWS Backup backs up in the primary account. The company configures cross-account backup in the Organizations management account. The company creates a new AWS account in the organization and configures an AWS Backup backup vault in the new account. The company creates a KMS key in the new account to encrypt the backups. Finally, the company configures a new backup plan in the primary account. The destination for the new backup plan is the backup vault in the new account. When the AWS Backup job in the primary account is invoked, the job creates backups in the primary account. However, the backups are not copied to the new account's backup vault. Which combination of steps must the company take so that backups can be copied to the new account's backup vault? (Select TWO.)

- A. Edit the backup vault access policy in the new account to allow access to the primary account.
- B. Edit the backup vault access policy in the primary account to allow access to the new account.
- C. Edit the backup vault access policy in the primary account to allow access to the KMS key in the new account.
- D. Edit the key policy of the KMS key in the primary account to share the key with the new account.
- E. Edit the key policy of the KMS key in the new account to share the key with the primary account.

**Answer:** AE

#### Explanation:

To enable cross-account backup, the company needs to grant permissions to both the backup vault and the KMS key in the destination account. The backup vault access policy in the destination account must allow the primary account to copy backups into the vault. The key policy of the KMS key in the destination account must allow the primary account to use the key to encrypt and decrypt the backups. These steps are described in the AWS documentation<sup>12</sup>. Therefore, the correct answer is A and E.

References:

- ? 1: Creating backup copies across AWS accounts - AWS Backup
- ? 2: Using AWS Backup with AWS Organizations - AWS Backup

#### NEW QUESTION 136

A company manages multiple AWS accounts in AWS Organizations. The company's security policy states that AWS account root user credentials for member accounts must not be used. The company monitors access to the root user credentials.

A recent alert shows that the root user in a member account launched an Amazon EC2 instance. A DevOps engineer must create an SCP at the organization's root level that will prevent the root user in member accounts from making any AWS service API calls.

Which SCP will meet these requirements?

A)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringNotLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

B)

```
"Version": "2012-10-17",
"Statement": [
  {
    "Effect": "Deny",
    "Action": "*",
    "Resource": "*",
    "Principal": { "AWS": "arn:aws:iam::*:root" }
  }
]
```

C)



```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

D)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Principal": "root"
    }
  ]
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer:** D

#### NEW QUESTION 137

An ecommerce company has chosen AWS to host its new platform. The company's DevOps team has started building an AWS Control Tower landing zone. The DevOps team has set the identity store within AWS IAM Identity Center (AWS Single Sign-On) to external identity provider (IdP) and has configured SAML 2.0. The DevOps team wants a robust permission model that applies the principle of least privilege. The model must allow the team to build and manage only the team's own resources.

Which combination of steps will meet these requirements? (Choose three.)

- A. Create IAM policies that include the required permission
- B. Include the aws:PrincipalTag condition key.
- C. Create permission set
- D. Attach an inline policy that includes the required permissions and uses the aws:PrincipalTag condition key to scope the permissions.
- E. Create a group in the Id
- F. Place users in the grou
- G. Assign the group to accounts and the permission sets in IAM Identity Center.
- H. Create a group in the Id
- I. Place users in the grou
- J. Assign the group to OUs and IAM policies.
- K. Enable attributes for access control in IAM Identity Cente
- L. Apply tags to user
- M. Map the tags as key-value pairs.
- N. Enable attributes for access control in IAM Identity Cente
- O. Map attributes from the IdP as key-value pairs.

**Answer:** BCF

#### Explanation:

Using the principalTag in the Permission Set inline policy a logged in user belonging to a specific AD group in the IDP can be permitted access to perform operations on certain resources if their group matches the group used in the PrincipleTag. Basically you are narrowing the scope of privileges assigned via Permission policies conditionally based on whether the logged in user belongs to a specific AD Group in IDP. The mapping of the AD group to the request attributes can be done using SSO attributes where we can pass other attributes like the SAML token as well.

<https://docs.aws.amazon.com/singlelogin/latest/userguide/abac.html>

#### NEW QUESTION 141

A company manages an application that stores logs in Amazon CloudWatch Logs. The company wants to archive the logs to an Amazon S3 bucket Logs are rarely accessed after 90 days and must be retained for 10 years.

Which combination of steps should a DevOps engineer take to meet these requirements? (Select TWO.)

- A. Configure a CloudWatch Logs subscription filter to use AWS Glue to transfer all logs to an S3 bucket.
- B. Configure a CloudWatch Logs subscription filter to use Amazon Kinesis Data Firehose to stream all logs to an S3 bucket.
- C. Configure a CloudWatch Logs subscription filter to stream all logs to an S3 bucket.
- D. Configure the S3 bucket lifecycle policy to transition logs to S3 Glacier after 90 days and to expire logs after 3.650 days.
- E. Configure the S3 bucket lifecycle policy to transition logs to Reduced Redundancy after 90 days and to expire logs after 3.650 days.

**Answer:** BD

**Explanation:**

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html>

**NEW QUESTION 146**

An application running on a set of Amazon EC2 instances in an Auto Scaling group requires a configuration file to operate. The instances are created and maintained with AWS CloudFormation. A DevOps engineer wants the instances to have the latest configuration file when launched and wants changes to the configuration file to be reflected on all the instances with a minimal delay when the CloudFormation template is updated. Company policy requires that application configuration files be maintained along with AWS infrastructure configuration files in source control.

Which solution will accomplish this?

- A. In the CloudFormation template add an AWS Config rule
- B. Place the configuration file content in the rule's InputParameters property and set the Scope property to the EC2 Auto Scaling group
- C. Add an AWS Systems Manager Resource Data Sync resource to the template to poll for updates to the configuration.
- D. In the CloudFormation template add an EC2 launch template resource
- E. Place the configuration file content in the launch template
- F. Configure the cfn-init script to run when the instance is launched and configure the cfn-hup script to poll for updates to the configuration.
- G. In the CloudFormation template add an EC2 launch template resource
- H. Place the configuration file content in the launch template
- I. Add an AWS Systems Manager Resource Data Sync resource to the template to poll for updates to the configuration.
- J. In the CloudFormation template add CloudFormation intrinsic metadata
- K. Place the configuration file content in the metadata
- L. Configure the cfn-init script to run when the instance is launched and configure the cfn-hup script to poll for updates to the configuration.

**Answer:** D

**Explanation:**

Use the AWS::CloudFormation::Init type to include metadata on an Amazon EC2 instance for the cfn-init helper script. If your template calls the cfn-init script, the script looks for resource metadata rooted in the AWS::CloudFormation::Init metadata key. Reference:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-resource-init.html>

**NEW QUESTION 148**

A development team wants to use AWS CloudFormation stacks to deploy an application. However, the developer IAM role does not have the required permissions to provision the resources that are specified in the AWS CloudFormation template. A DevOps engineer needs to implement a solution that allows the developers to deploy the stacks. The solution must follow the principle of least privilege.

Which solution will meet these requirements?

- A. Create an IAM policy that allows the developers to provision the required resource
- B. Attach the policy to the developer IAM role.
- C. Create an IAM policy that allows full access to AWS CloudFormation
- D. Attach the policy to the developer IAM role.
- E. Create an AWS CloudFormation service role that has the required permission
- F. Grant the developer IAM role a cloudformation:\* action
- G. Use the new service role during stack deployments.
- H. Create an AWS CloudFormation service role that has the required permission
- I. Grant the developer IAM role the iam:PassRole permission
- J. Use the new service role during stack deployments.

**Answer:** D

**Explanation:**

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-iam-service-role.html>

**NEW QUESTION 153**

A company uses AWS Secrets Manager to store a set of sensitive API keys that an AWS Lambda function uses. When the Lambda function is invoked, the Lambda function retrieves the API keys and makes an API call to an external service. The Secrets Manager secret is encrypted with the default AWS Key Management Service (AWS KMS) key.

A DevOps engineer needs to update the infrastructure to ensure that only the Lambda function's execution role can access the values in Secrets Manager. The solution must apply the principle of least privilege.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Update the default KMS key for Secrets Manager to allow only the Lambda function's execution role to decrypt.
- B. Create a KMS customer managed key that trusts Secrets Manager and allows the Lambda function's execution role to decrypt
- C. Update Secrets Manager to use the new customer managed key.
- D. Create a KMS customer managed key that trusts Secrets Manager and allows the account's root principal to decrypt
- E. Update Secrets Manager to use the new customer managed key.
- F. Ensure that the Lambda function's execution role has the KMS permissions scoped on the resource level
- G. Configure the permissions so that the KMS key can encrypt the Secrets Manager secret.
- H. Remove all KMS permissions from the Lambda function's execution role.

**Answer:** BD

**Explanation:**

The requirement is to update the infrastructure to ensure that only the Lambda function's execution role can access the values in Secrets Manager. The solution must apply the principle of least privilege, which means granting the minimum permissions necessary to perform a task.

To do this, the DevOps engineer needs to use the following steps:

? Create a KMS customer managed key that trusts Secrets Manager and allows the Lambda function's execution role to decrypt. A customer managed key is a symmetric encryption key that is fully managed by the customer. The customer can define the key policy, which specifies who can use and manage the key. By creating a customer managed key, the DevOps engineer can restrict the decryption permission to only the Lambda function's execution role, and prevent other principals from accessing the secret values. The customer managed key also needs to trust Secrets Manager, which means allowing Secrets Manager to use the key to encrypt and decrypt secrets on behalf of the customer.

? Update Secrets Manager to use the new customer managed key. Secrets Manager allows customers to choose which KMS key to use for encrypting each secret. By default, Secrets Manager uses the default KMS key for Secrets Manager, which is a service-managed key that is shared by all customers in the same AWS Region. By updating Secrets Manager to use the new customer managed key, the DevOps engineer can ensure that only the Lambda function's execution role can decrypt the secret values using that key.

? Ensure that the Lambda function's execution role has the KMS permissions scoped on the resource level. The Lambda function's execution role is an IAM role that grants permissions to the Lambda function to access AWS services and resources. The role needs to have KMS permissions to use the customer managed key for decryption. However, to apply the principle of least privilege, the role should have the permissions scoped on the resource level, which means specifying the ARN of the customer managed key as a condition in the IAM policy statement. This way, the role can only use that specific key and not any other KMS keys in the account.

## NEW QUESTION 155

.....



## THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual DOP-C02 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the DOP-C02 Product From:

<https://www.2passeasy.com/dumps/DOP-C02/>

## Money Back Guarantee

### DOP-C02 Practice Exam Features:

- \* DOP-C02 Questions and Answers Updated Frequently
- \* DOP-C02 Practice Questions Verified by Expert Senior Certified Staff
- \* DOP-C02 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* DOP-C02 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year