

# CompTIA

## Exam Questions SY0-701

CompTIA Security+ Exam



### NEW QUESTION 1

Employees in the research and development business unit receive extensive training to ensure they understand how to best protect company data. Which of the following is the type of data these employees are most likely to use in day-to-day work activities?

- A. Encrypted
- B. Intellectual property
- C. Critical
- D. Data in transit

**Answer: B**

#### Explanation:

Intellectual property is a type of data that consists of ideas, inventions, designs, or other creative works that have commercial value and are protected by law. Employees in the research and development business unit are most likely to use intellectual property data in their day-to-day work activities, as they are involved in creating new products or services for the company. Intellectual property data needs to be protected from unauthorized use, disclosure, or theft, as it can give the company a competitive advantage in the market. Therefore, these employees receive extensive training to ensure they understand how to best protect this type of data. References = CompTIA Security+ SY0-701 Certification Study Guide, page 90; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 1.2 - Security Concepts, 7:57 - 9:03.

### NEW QUESTION 2

Which of the following must be considered when designing a high-availability network? (Choose two).

- A. Ease of recovery
- B. Ability to patch
- C. Physical isolation
- D. Responsiveness
- E. Attack surface
- F. Extensible authentication

**Answer: AE**

#### Explanation:

A high-availability network is a network that is designed to minimize downtime and ensure continuous operation even in the event of a failure or disruption. A high-availability network must consider the following factors:

? Ease of recovery: This refers to the ability of the network to restore normal functionality quickly and efficiently after a failure or disruption. Ease of recovery can be achieved by implementing backup and restore procedures, redundancy and failover mechanisms, fault tolerance and resilience, and disaster recovery plans.

? Attack surface: This refers to the amount of exposure and vulnerability of the network to potential threats and attacks. Attack surface can be reduced by implementing security controls such as firewalls, encryption, authentication, access control, segmentation, and hardening.

The other options are not directly related to high-availability network design:

? Ability to patch: This refers to the process of updating and fixing software components to address security issues, bugs, or performance improvements. Ability to patch is important for maintaining the security and functionality of the network, but it is not a specific factor for high-availability network design.

? Physical isolation: This refers to the separation of network components or devices from other networks or physical environments. Physical isolation can enhance the security and performance of the network, but it can also reduce the availability and accessibility of the network resources.

? Responsiveness: This refers to the speed and quality of the network's performance and service delivery. Responsiveness can be measured by metrics such as latency, throughput, jitter, and packet loss. Responsiveness is important for ensuring customer satisfaction and user experience, but it is not a specific factor for high-availability network design.

? Extensible authentication: This refers to the ability of the network to support multiple and flexible authentication methods and protocols. Extensible authentication can improve the security and convenience of the network, but it is not a specific factor for high-availability network design.

References = 1: CompTIA Security+ SY0-701 Certification Study Guide, page 972: High Availability – CompTIA Security+ SY0-701 – 3.4, video by Professor Messer.

### NEW QUESTION 3

Which of the following describes the process of concealing code or text inside a graphical image?

- A. Symmetric encryption
- B. Hashing
- C. Data masking
- D. Steganography

**Answer: D**

#### Explanation:

Steganography is the process of hiding information within another medium, such as an image, audio, video, or text file. The hidden information is not visible or noticeable to the casual observer, and can only be extracted by using a specific technique or key. Steganography can be used for various purposes, such as concealing secret messages, watermarking, or evading detection by antivirus software.

References:

1: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 5: Cryptography and PKI, page 233 2: CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 5: Cryptography and PKI, page 235

### NEW QUESTION 4

Which of the following enables the use of an input field to run commands that can view or manipulate data?

- A. Cross-site scripting
- B. Side loading
- C. Buffer overflow
- D. SQL injection

**Answer:** D

**Explanation:**

= SQL injection is a type of attack that enables the use of an input field to run commands that can view or manipulate data in a database. SQL stands for Structured Query Language, which is a language used to communicate with databases. By injecting malicious SQL statements into an input field, an attacker can bypass authentication, access sensitive information, modify or delete data, or execute commands on the server. SQL injection is one of the most common and dangerous web application vulnerabilities. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 5, page 195. CompTIA Security+ SY0-701 Exam Objectives, Domain 1.1, page 8.

**NEW QUESTION 5**

Which of the following describes a security alerting and monitoring tool that collects system, application, and network logs from multiple sources in a centralized system?

- A. SIEM
- B. DLP
- C. IDS
- D. SNMP

**Answer:** A

**Explanation:**

SIEM stands for Security Information and Event Management. It is a security alerting and monitoring tool that collects system, application, and network logs from multiple sources in a centralized system. SIEM can analyze the collected data, correlate events, generate alerts, and provide reports and dashboards. SIEM can also integrate with other security tools and support compliance requirements. SIEM helps organizations to detect and respond to cyber threats, improve security posture, and reduce operational costs. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 10: Monitoring and Auditing, page 393. CompTIA Security+ Practice Tests: Exam SY0-701, 3rd Edition, Chapter 10: Monitoring and Auditing, page 397.

**NEW QUESTION 6**

A security consultant needs secure, remote access to a client environment. Which of the following should the security consultant most likely use to gain access?

- A. EAP
- B. DHCP
- C. IPSec
- D. NAT

**Answer:** C

**Explanation:**

IPSec is a protocol suite that provides secure communication over IP networks. IPSec can be used to create virtual private networks (VPNs) that encrypt and authenticate the data exchanged between two or more parties. IPSec can also provide data integrity, confidentiality, replay protection, and access control. A security consultant can use IPSec to gain secure, remote access to a client environment by establishing a VPN tunnel with the client's network. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 8: Secure Protocols and Services, page 385 1

**NEW QUESTION 7**

A company's web filter is configured to scan the URL for strings and deny access when matches are found. Which of the following search strings should an analyst employ to prohibit access to non-encrypted websites?

- A. encryption=off\
- B. http://
- C. www.\*.com
- D. :443

**Answer:** B

**Explanation:**

A web filter is a device or software that can monitor, block, or allow web traffic based on predefined rules or policies. One of the common methods of web filtering is to scan the URL for strings and deny access when matches are found. For example, a web filter can block access to websites that contain the words "gambling", "porn", or "malware" in their URLs. A URL is a uniform resource locator that identifies the location and protocol of a web resource. A URL typically consists of the following components: protocol://domain:port/path?query#fragment. The protocol specifies the communication method used to access the web resource, such as HTTP, HTTPS, FTP, or SMTP. The domain is the name of the web server that hosts the web resource, such as www.google.com or www.bing.com. The port is an optional number that identifies the specific service or application running on the web server, such as 80 for HTTP or 443 for HTTPS. The path is the specific folder or file name of the web resource, such as /index.html or /images/logo.png. The query is an optional string that contains additional information or parameters for the web resource, such as ?q=security or ?lang=en. The fragment is an optional string that identifies a specific part or section of the web resource, such as #introduction or #summary.

To prohibit access to non-encrypted websites, an analyst should employ a search string that matches the protocol of non-encrypted web traffic, which is HTTP. HTTP stands for hypertext transfer protocol, and it is a standard protocol for transferring data between web servers and web browsers. However, HTTP does not provide any encryption or security for the data, which means that anyone who intercepts the web traffic can read or modify the data. Therefore, non-encrypted websites are vulnerable to eavesdropping, tampering, or spoofing attacks. To access a non-encrypted website, the URL usually starts with http://, followed by the domain name and optionally the port number. For example, http://www.example.com or http://www.example.com:80. By scanning the URL for the string http://, the web filter can identify and block non-encrypted websites.

The other options are not correct because they do not match the protocol of non-encrypted web traffic. Encryption=off is a possible query string that indicates the encryption status of the web resource, but it is not a standard or mandatory parameter. https:// is the protocol of encrypted web traffic, which uses hypertext transfer protocol secure (HTTPS) to provide encryption and security for the data. www.\*.com is a possible domain name that matches any website that starts with www and ends with .com, but it does not specify the protocol.

:443 is the port number of HTTPS, which is the protocol of encrypted web traffic. References = CompTIA Security+ Study Guide (SY0-701), Chapter 2: Securing Networks, page 69. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 2.1: Network Devices and Technologies, video: Web Filter (5:16).

**NEW QUESTION 8**

After a recent vulnerability scan, a security engineer needs to harden the routers within the corporate network. Which of the following is the most appropriate to disable?

- A. Console access
- B. Routing protocols
- C. VLANs
- D. Web-based administration

**Answer: D**

**Explanation:**

Web-based administration is a feature that allows users to configure and manage routers through a web browser interface. While this feature can provide convenience and ease of use, it can also pose a security risk, especially if the web interface is exposed to the internet or uses weak authentication or encryption methods. Web-based administration can be exploited by attackers to gain unauthorized access to the router's settings, firmware, or data, or to launch attacks such as cross-site scripting (XSS) or cross-site request forgery (CSRF). Therefore, disabling web-based administration is a good practice to harden the routers within the corporate network. Console access, routing protocols, and VLANs are other features that can be configured on routers, but they are not the most appropriate to disable for hardening purposes. Console access is a physical connection to the router that requires direct access to the device, which can be secured by locking the router in a cabinet or using a strong password. Routing protocols are essential for routers to exchange routing information and maintain network connectivity, and they can be secured by using authentication or encryption mechanisms. VLANs are logical segments of a network that can enhance network performance and security by isolating traffic and devices, and they can be secured by using VLAN access control lists (VACLs) or private VLANs (PVLANS). References: CCNA SEC: Router Hardening Your Router's Security Stinks: Here's How to Fix It

**NEW QUESTION 9**

A company purchased cyber insurance to address items listed on the risk register. Which of the following strategies does this represent?

- A. Accept
- B. Transfer
- C. Mitigate
- D. Avoid

**Answer: B**

**Explanation:**

Cyber insurance is a type of insurance that covers the financial losses and liabilities that result from cyberattacks, such as data breaches, ransomware, denial-of-service, phishing, or malware. Cyber insurance can help a company recover from the costs of restoring data, repairing systems, paying ransoms, compensating customers, or facing legal actions. Cyber insurance is one of the possible strategies that a company can use to address the items listed on the risk register. A risk register is a document that records the identified risks, their probability, impact, and mitigation strategies for a project or an organization. The four common risk mitigation strategies are:

? Accept: The company acknowledges the risk and decides to accept the consequences without taking any action to reduce or eliminate the risk. This strategy is usually chosen when the risk is low or the cost of mitigation is too high.

? Transfer: The company transfers the risk to a third party, such as an insurance company, a vendor, or a partner. This strategy is usually chosen when the risk is high or the company lacks the resources or expertise to handle the risk.

? Mitigate: The company implements controls or measures to reduce the likelihood or impact of the risk. This strategy is usually chosen when the risk is moderate or the cost of mitigation is reasonable.

? Avoid: The company eliminates the risk by changing the scope, plan, or design of the project or the organization. This strategy is usually chosen when the risk is unacceptable or the cost of mitigation is too high.

By purchasing cyber insurance, the company is transferring the risk to the insurance company, which will cover the financial losses and liabilities in case of a cyberattack. Therefore, the correct answer is B. Transfer. References = CompTIA Security+ Study Guide (SY0-701), Chapter 8: Governance, Risk, and Compliance, page 377. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 8.1: Risk Management, video: Risk Mitigation Strategies (5:37).

**NEW QUESTION 10**

A systems administrator is working on a solution with the following requirements:

- Provide a secure zone.
- Enforce a company-wide access control policy.
- Reduce the scope of threats.

Which of the following is the systems administrator setting up?

- A. Zero Trust
- B. AAA
- C. Non-repudiation
- D. CIA

**Answer: A**

**Explanation:**

Zero Trust is a security model that assumes no trust for any entity inside or outside the network perimeter and requires continuous verification of identity and permissions. Zero Trust can provide a secure zone by isolating and protecting sensitive data and resources from unauthorized access. Zero Trust can also enforce a company-wide access control policy by applying the principle of least privilege and granular segmentation for users, devices, and applications. Zero Trust can reduce the scope of threats by preventing lateral movement and minimizing the attack surface.

References:

? 5: This source explains the concept and benefits of Zero Trust security and how it differs from traditional security models.

? 8: This source provides an overview of Zero Trust identity security and how it can help verify the identity and integrity of users and devices.

**NEW QUESTION 10**

A company needs to provide administrative access to internal resources while minimizing the traffic allowed through the security boundary. Which of the following methods is most secure?

- A. Implementing a bastion host
- B. Deploying a perimeter network
- C. Installing a WAF

D. Utilizing single sign-on

**Answer:** A

**Explanation:**

A bastion host is a special-purpose server that is designed to withstand attacks and provide secure access to internal resources. A bastion host is usually placed on the edge of a network, acting as a gateway or proxy to the internal network. A bastion host can be configured to allow only certain types of traffic, such as SSH or HTTP, and block all other traffic. A bastion host can also run security software such as firewalls, intrusion detection systems, and antivirus programs to monitor and filter incoming and outgoing traffic. A bastion host can provide administrative access to internal resources by requiring strong authentication and encryption, and by logging all activities for auditing purposes<sup>12</sup>.

A bastion host is the most secure method among the given options because it minimizes the traffic allowed through the security boundary and provides a single point of control and defense. A bastion host can also isolate the internal network from direct exposure to the internet or other untrusted networks, reducing the attack surface and the risk of compromise<sup>3</sup>.

Deploying a perimeter network is not the correct answer, because a perimeter network is a network segment that separates the internal network from the external network. A perimeter network usually hosts public-facing services such as web servers, email servers, or DNS servers that need to be accessible from the internet. A perimeter network does not provide administrative access to internal resources, but rather protects them from unauthorized access. A perimeter network can also increase the complexity and cost of network management and security<sup>4</sup>.

Installing a WAF is not the correct answer, because a WAF is a security tool that protects web applications from common web-based attacks by monitoring, filtering, and blocking HTTP traffic. A WAF can prevent attacks such as cross-site scripting, SQL injection, or file inclusion, among others. A WAF does not provide administrative access to internal resources, but rather protects them from web application vulnerabilities. A WAF is also not a comprehensive solution for network security, as it only operates at the application layer and does not protect against other types of attacks or threats<sup>5</sup>.

Utilizing single sign-on is not the correct answer, because single sign-on is a method of authentication that allows users to access multiple sites, services, or applications with one username and password. Single sign-on can simplify the sign-in process for users and reduce the number of passwords they have to remember and manage. Single sign-on does not provide administrative access to internal resources, but rather enables access to various resources that the user is authorized to use. Single sign-on can also introduce security risks if the user's credentials are compromised or if the single sign-on provider is breached<sup>6</sup>. References = 1: Bastion host - Wikipedia, 2: 14 Best Practices to Secure SSH Bastion Host - goteleport.com, 3: The Importance Of Bastion Hosts In Network

Security, 4: What is the network perimeter? | Cloudflare, 5: What is a WAF? | Web Application Firewall explained, 6: [What is single sign-on (SSO)? - Definition from WhatIs.com]

**NEW QUESTION 14**

Which of the following are cases in which an engineer should recommend the decommissioning of a network device? (Select two).

- A. The device has been moved from a production environment to a test environment.
- B. The device is configured to use cleartext passwords.
- C. The device is moved to an isolated segment on the enterprise network.
- D. The device is moved to a different location in the enterprise.
- E. The device's encryption level cannot meet organizational standards.
- F. The device is unable to receive authorized updates.

**Answer:** E

**Explanation:**

An engineer should recommend the decommissioning of a network device when the device poses a security risk or a compliance violation to the enterprise environment. A device that cannot meet the encryption standards or receive authorized updates is vulnerable to attacks and breaches, and may expose sensitive data or compromise network integrity. Therefore, such a device should be removed from the network and replaced with a more secure and updated one.

References

? CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 2, Section 2.2, page 671

? CompTIA Security+ Practice Tests: Exam SY0-701, 3rd Edition, Chapter 2,

Question 16, page 512

**NEW QUESTION 16**

A company requires hard drives to be securely wiped before sending decommissioned systems to recycling. Which of the following best describes this policy?

- A. Enumeration
- B. Sanitization
- C. Destruction
- D. Inventory

**Answer:** B

**Explanation:**

Sanitization is the process of removing sensitive data from a storage device or a system before it is disposed of or reused. Sanitization can be done by using software tools or hardware devices that overwrite the data with random patterns or zeros, making it unrecoverable. Sanitization is different from destruction, which is the physical damage of the storage device to render it unusable. Sanitization is also different from enumeration, which is the identification of network resources or devices, and inventory, which is the tracking of assets and their locations. The policy of securely wiping hard drives before sending decommissioned systems to recycling is an example of sanitization, as it ensures that no confidential data can be retrieved from the recycled devices. References = Secure Data Destruction – SY0-601 CompTIA Security+ : 2.7, video at 1:00; CompTIA Security+ SY0-701 Certification Study Guide, page 387.

**NEW QUESTION 21**

Which of the following would be the best way to block unknown programs from executing?

- A. Access control list
- B. Application allow list.
- C. Host-based firewall
- D. DLP solution

**Answer:** B

**Explanation:**

An application allow list is a security technique that specifies which applications are permitted to run on a system or a network. An application allow list can block unknown programs from executing by only allowing the execution of programs that are explicitly authorized and verified. An application allow list can prevent malware, unauthorized software, or unwanted applications from running and compromising the security of the system or the network<sup>12</sup>.

The other options are not the best ways to block unknown programs from executing:

? Access control list: This is a security technique that specifies which users or groups are granted or denied access to a resource or an object. An access control list can control the permissions and privileges of users or groups, but it does not directly block unknown programs from executing<sup>13</sup>.

? Host-based firewall: This is a security device that monitors and filters the incoming and outgoing network traffic on a single host or system. A host-based firewall can block or allow network connections based on predefined rules, but it does not directly block unknown programs from executing<sup>1</sup>.

? DLP solution: This is a security system that detects and prevents the unauthorized transmission or leakage of sensitive data. A DLP solution can protect the confidentiality and integrity of data, but it does not directly block unknown programs from executing<sup>1</sup>.

References = 1: CompTIA Security+ SY0-701 Certification Study Guide, page 972: Application Whitelisting – CompTIA Security+ SY0-701 – 3.5, video by Professor Messer<sup>3</sup>: CompTIA Security+ SY0-701 Certification Study Guide, page 98. : CompTIA Security+ SY0-701 Certification Study Guide, page 99. : CompTIA Security+ SY0-701 Certification Study Guide, page 100.

### NEW QUESTION 25

During a security incident, the security operations team identified sustained network traffic from a malicious IP address: 10.1.4.9. A security analyst is creating an inbound firewall rule to block the IP address from accessing the organization's network. Which of the following fulfills this request?

- A. access-list inbound deny ig source 0.0.0.0/0 destination 10.1.4.9/32
- B. access-list inbound deny ig source 10.1.4.9/32 destination 0.0.0.0/0
- C. access-list inbound permit ig source 10.1.4.9/32 destination 0.0.0.0/0
- D. access-list inbound permit ig source 0.0.0.0/0 destination 10.1.4.9/32

**Answer: B**

#### Explanation:

A firewall rule is a set of criteria that determines whether to allow or deny a packet to pass through the firewall. A firewall rule consists of several elements, such as the action, the protocol, the source address, the destination address, and the port number. The syntax of a firewall rule may vary depending on the type and vendor of the firewall, but the basic logic is the same. In this question, the security analyst is creating an inbound firewall rule to block the IP address 10.1.4.9 from accessing the organization's network. This means that the action should be deny, the protocol should be any (or ig for IP), the source address should be 10.1.4.9/32 (which means a single IP address), the destination address should be 0.0.0.0/0 (which means any IP address), and the port number should be any. Therefore, the correct firewall rule is:

```
access-list inbound deny ig source 10.1.4.9/32 destination 0.0.0.0/0
```

This rule will match any packet that has the source IP address of 10.1.4.9 and drop it. The other options are incorrect because they either have the wrong action, the wrong source address, or the wrong destination address. For example, option A has the source and destination addresses reversed, which means that it will block any packet that has the destination IP address of 10.1.4.9, which is not the intended goal. Option C has the wrong action, which is permit, which means that it will allow the packet to pass through the firewall, which is also not the intended goal. Option D has the same problem as option A, with the source and destination addresses reversed.

References = Firewall Rules – CompTIA Security+ SY0-401: 1.2, Firewalls – SY0-601 CompTIA Security+ : 3.3, Firewalls – CompTIA Security+ SY0-501, Understanding Firewall Rules – CompTIA Network+ N10-005: 5.5, Configuring Windows Firewall – CompTIA A+ 220-1102 – 1.6.

### NEW QUESTION 30

An organization is building a new backup data center with cost-benefit as the primary requirement and RTO and RPO values around two days. Which of the following types of sites is the best for this scenario?

- A. Real-time recovery
- B. Hot
- C. Cold
- D. Warm

**Answer: C**

#### Explanation:

A cold site is a type of backup data center that has the necessary infrastructure to support IT operations, but does not have any pre-configured hardware or software. A cold site is the cheapest option among the backup data center types, but it also has the longest recovery time objective (RTO) and recovery point objective (RPO) values. A cold site is suitable for scenarios where the cost-benefit is the primary requirement and the RTO and RPO values are not very stringent. A cold site can take up to two days or more to restore the normal operations after a disaster. References = CompTIA Security+ SY0-701 Certification Study Guide, page 387; Backup Types – SY0-601 CompTIA Security+ : 2.5, video at 4:50.

### NEW QUESTION 33

A security analyst and the management team are reviewing the organizational performance of a recent phishing campaign. The user click-through rate exceeded the acceptable risk threshold, and the management team wants to reduce the impact when a user clicks on a link in a phishing message. Which of the following should the analyst do?

- A. Place posters around the office to raise awareness of common phishing activities.
- B. Implement email security filters to prevent phishing emails from being delivered
- C. Update the EDR policies to block automatic execution of downloaded programs.
- D. Create additional training for users to recognize the signs of phishing attempts.

**Answer: C**

#### Explanation:

An endpoint detection and response (EDR) system is a security tool that monitors and analyzes the activities and behaviors of endpoints, such as computers, laptops, mobile devices, and servers. An EDR system can detect, prevent, and respond to various types of threats, such as malware, ransomware, phishing, and advanced persistent threats (APTs). One of the features of an EDR system is to block the automatic execution of downloaded programs, which can prevent malicious code from running on the endpoint when a user clicks on a link in a phishing message. This can reduce the impact of a phishing attack and protect the endpoint from compromise. Updating the EDR policies to block automatic execution of downloaded programs is a technical control that can mitigate the risk of phishing, regardless of the user's awareness or behavior. Therefore, this is the best answer among the given options.

The other options are not as effective as updating the EDR policies, because they rely on administrative or physical controls that may not be sufficient to prevent or stop a phishing attack. Placing posters around the office to raise awareness of common phishing activities is a physical control that can increase the user's

knowledge of phishing, but it may not change their behavior or prevent them from clicking on a link in a phishing message. Implementing email security filters to prevent phishing emails from being delivered is an administrative control that can reduce the exposure to phishing, but it may not be able to block all phishing emails, especially if they are crafted to bypass the filters. Creating additional training for users to recognize the signs of phishing attempts is an administrative control that can improve the user's skills of phishing detection, but it may not guarantee that they will always be vigilant or cautious when receiving an email. Therefore, these options are not the best answer for this question. References = Endpoint Detection and Response – CompTIA Security+ SY0-701 – 2.2, video at 5:30; CompTIA Security+ SY0-701 Certification Study Guide, page 163.

#### NEW QUESTION 34

Which of the following tools can assist with detecting an employee who has accidentally emailed a file containing a customer's PII?

- A. SCAP
- B. Net Flow
- C. Antivirus
- D. DLP

**Answer: D**

#### Explanation:

DLP stands for Data Loss Prevention, which is a tool that can assist with detecting and preventing the unauthorized transmission or leakage of sensitive data, such as a customer's PII (Personally Identifiable Information). DLP can monitor, filter, and block data in motion (such as emails), data at rest (such as files), and data in use (such as applications). DLP can also alert the sender, the recipient, or the administrator of the data breach, and apply remediation actions, such as encryption, quarantine, or deletion. DLP can help an organization comply with data protection regulations, such as GDPR, HIPAA, or PCI DSS, and protect its reputation and assets. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 78. CompTIA Security+ SY0-701 Exam Objectives, Domain 2.5, page 11.

#### NEW QUESTION 38

The marketing department set up its own project management software without telling the appropriate departments. Which of the following describes this scenario?

- A. Shadow IT
- B. Insider threat
- C. Data exfiltration
- D. Service disruption

**Answer: A**

#### Explanation:

Shadow IT is the term used to describe the use of unauthorized or unapproved IT resources within an organization. The marketing department set up its own project management software without telling the appropriate departments, such as IT, security, or compliance. This could pose a risk to the organization's security posture, data integrity, and regulatory compliance.

References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 2, page 35.

#### NEW QUESTION 39

After an audit, an administrator discovers all users have access to confidential data on a file server. Which of the following should the administrator use to restrict access to the data quickly?

- A. Group Policy
- B. Content filtering
- C. Data loss prevention
- D. Access control lists

**Answer: D**

#### Explanation:

Access control lists (ACLs) are rules that specify which users or groups can access which resources on a file server. They can help restrict access to confidential data by granting or denying permissions based on the identity or role of the user. In this case, the administrator can use ACLs to quickly modify the access rights of the users and prevent them from accessing the data they are not authorized to

see. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 308 1

#### NEW QUESTION 41

An organization recently updated its security policy to include the following statement:

Regular expressions are included in source code to remove special characters such as \$, |, ;, &, ` , and ? from variables set by forms in a web application.

Which of the following best explains the security technique the organization adopted by making this addition to the policy?

- A. Identify embedded keys
- B. Code debugging
- C. Input validation
- D. Static code analysis

**Answer: C**

#### Explanation:

Input validation is a security technique that checks the user input for any malicious or unexpected data before processing it by the application. Input validation can prevent various types of attacks, such as injection, cross-site scripting, buffer overflow, and command execution, that exploit the vulnerabilities in the application code. Input validation can be performed on both the client-side and the server-side, using methods such as whitelisting, blacklisting, filtering, sanitizing, escaping, and encoding. By including regular expressions in the source code to remove special characters from the variables set by the forms in the web application, the organization adopted input validation as a security technique. Regular expressions are patterns that match a specific set of characters or strings, and can be used to filter out any unwanted or harmful input. Special characters, such as \$, |, ;, &, ` , and ? , can be used by attackers to inject commands or scripts into the application, and cause damage or data theft. By removing these characters from the input, the organization can reduce the risk of such attacks.

Identify embedded keys, code debugging, and static code analysis are not the security techniques that the organization adopted by making this addition to the

policy. Identify embedded keys is a process of finding and removing any hard-coded keys or credentials from the source code, as these can pose a security risk if exposed or compromised. Code debugging is a process of finding and fixing any errors or bugs in the source code, which can affect the functionality or performance of the application. Static code analysis is a process of analyzing the source code without executing it, to identify any vulnerabilities, flaws, or coding standards violations. These techniques are not related to the use of regular expressions to remove special characters from the input.

References = CompTIA Security+ SY0-701 Certification Study Guide, page 375-376; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 4.1 - Vulnerability Scanning, 8:00 - 9:08; Application Security – SY0-601 CompTIA Security+ : 3.2, 0:00 - 2:00.

#### NEW QUESTION 46

A security administrator is deploying a DLP solution to prevent the exfiltration of sensitive customer data. Which of the following should the administrator do first?

- A. Block access to cloud storage websites.
- B. Create a rule to block outgoing email attachments.
- C. Apply classifications to the data.
- D. Remove all user permissions from shares on the file server.

**Answer: C**

#### Explanation:

Data classification is the process of assigning labels or tags to data based on its sensitivity, value, and risk. Data classification is the first step in a data loss prevention (DLP) solution, as it helps to identify what data needs to be protected and how. By applying classifications to the data, the security administrator can define appropriate policies and rules for the DLP solution to prevent the exfiltration of sensitive customer data. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 8: Data Protection, page 323. CompTIA Security+ Practice Tests: Exam SY0-701, 3rd Edition, Chapter 8: Data Protection, page 327.

#### NEW QUESTION 50

A technician needs to apply a high-priority patch to a production system. Which of the following steps should be taken first?

- A. Air gap the system.
- B. Move the system to a different network segment.
- C. Create a change control request.
- D. Apply the patch to the system.

**Answer: C**

#### Explanation:

= A change control request is a document that describes the proposed change to a system, the reason for the change, the expected impact, the approval process, the testing plan, the implementation plan, the rollback plan, and the communication plan. A change control request is a best practice for applying any patch to a production system, especially a high-priority one, as it ensures that the change is authorized, documented, tested, and communicated. A change control request also minimizes the risk of unintended consequences, such as system downtime, data loss, or security breaches. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 6, page 235. CompTIA Security+ SY0-701 Exam Objectives, Domain 4.1, page 13.

#### NEW QUESTION 55

Which of the following is the most likely to be included as an element of communication in a security awareness program?

- A. Reporting phishing attempts or other suspicious activities
- B. Detecting insider threats using anomalous behavior recognition
- C. Verifying information when modifying wire transfer data
- D. Performing social engineering as part of third-party penetration testing

**Answer: A**

#### Explanation:

A security awareness program is a set of activities and initiatives that aim to educate and inform the users and employees of an organization about the security policies, procedures, and best practices. A security awareness program can help to reduce the human factor in security risks, such as social engineering, phishing, malware, data breaches, and insider threats. A security awareness program should include various elements of communication, such as newsletters, posters, videos, webinars, quizzes, games, simulations, and feedback mechanisms, to deliver the security messages and reinforce the security culture. One of the most likely elements of communication to be included in a security awareness program is reporting phishing attempts or other suspicious activities, as this can help to raise the awareness of the users and employees about the common types of cyberattacks and how to respond to them. Reporting phishing attempts or other suspicious activities can also help to alert the security team and enable them to take appropriate actions to prevent or mitigate the impact of the attacks. Therefore, this is the best answer among the given options.

The other options are not as likely to be included as elements of communication in a security awareness program, because they are either technical or operational tasks that are not directly related to the security awareness of the users and employees. Detecting insider threats using anomalous behavior recognition is a technical task that involves using security tools or systems to monitor and analyze the activities and behaviors of the users and employees and identify any deviations or anomalies that may indicate malicious or unauthorized actions. This task is usually performed by the security team or the security operations center, and it does not require the communication or participation of the users and employees. Verifying information when modifying wire transfer data is an operational task that involves using verification methods, such as phone calls, emails, or digital signatures, to confirm the authenticity and accuracy of the information related to wire transfers, such as the account number, the amount, or the recipient. This task is usually performed by the financial or accounting department, and it does not involve the security awareness of the users and employees. Performing social engineering as part of third-party penetration testing is a technical task that involves using deception or manipulation techniques, such as phishing, vishing, or impersonation, to test the security posture and the vulnerability of the users and employees to social engineering attacks. This task is usually performed by external security professionals or consultants, and it does not require the communication or consent of the users and employees. Therefore, these options are not the best answer for this question. References = Security Awareness and Training –

CompTIA Security+ SY0-701: 5.2, video at 0:00; CompTIA Security+ SY0-701 Certification Study Guide, page 263.

#### NEW QUESTION 56

An administrator discovers that some files on a database server were recently encrypted. The administrator sees from the security logs that the data was last accessed by a domain user. Which of the following best describes the type of attack that occurred?

- A. Insider threat

- B. Social engineering
- C. Watering-hole
- D. Unauthorized attacker

**Answer:** A

**Explanation:**

An insider threat is a type of attack that originates from someone who has legitimate access to an organization's network, systems, or data. In this case, the domain user who encrypted the files on the database server is an example of an insider threat, as they abused their access privileges to cause harm to the organization. Insider threats can be motivated by various factors, such as financial gain, revenge, espionage, or sabotage. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 1: General Security Concepts, page 251. CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 1: General Security Concepts, page 252.

**NEW QUESTION 57**

A company hired a consultant to perform an offensive security assessment covering penetration testing and social engineering. Which of the following teams will conduct this assessment activity?

- A. White
- B. Purple
- C. Blue
- D. Red

**Answer:** D

**Explanation:**

A red team is a group of security professionals who perform offensive security assessments covering penetration testing and social engineering. A red team simulates real-world attacks and exploits the vulnerabilities of a target organization, system, or network. A red team aims to test the effectiveness of the security controls, policies, and procedures of the target, as well as the awareness and response of the staff and the blue team. A red team can be hired as an external consultant or formed internally within the organization. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 1, page 18. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 1.8, page 4. Security Teams – SY0-601 CompTIA Security+ : 1.8

**NEW QUESTION 59**

Which of the following threat actors is the most likely to use large financial resources to attack critical systems located in other countries?

- A. Insider
- B. Unskilled attacker
- C. Nation-state
- D. Hactivist

**Answer:** C

**Explanation:**

A nation-state is a threat actor that is sponsored by a government or a political entity to conduct cyberattacks against other countries or organizations. Nation-states have large financial resources, advanced technical skills, and strategic objectives that may target critical systems such as military, energy, or infrastructure. Nation-states are often motivated by espionage, sabotage, or warfare<sup>12</sup>. References = 1: CompTIA Security+ SY0-701 Certification Study Guide, page 542: Threat Actors – CompTIA Security+ SY0-701 – 2.1, video by Professor Messer.

**NEW QUESTION 62**

Which of the following security control types does an acceptable use policy best represent?

- A. Detective
- B. Compensating
- C. Corrective
- D. Preventive

**Answer:** D

**Explanation:**

An acceptable use policy (AUP) is a set of rules that govern how users can access and use a corporate network or the internet. The AUP helps companies minimize their exposure to cyber security threats and limit other risks. The AUP also serves as a notice to users about what they are not allowed to do and protects the company against misuse of their network. Users usually have to acknowledge that they understand and agree to the rules before accessing the network<sup>1</sup>. An AUP best represents a preventive security control type, because it aims to deter or stop potential security incidents from occurring in the first place. A preventive control is proactive and anticipates possible threats and vulnerabilities, and implements measures to prevent them from exploiting or harming the system or the data. A preventive control can be physical, technical, or administrative in nature<sup>2</sup>.

Some examples of preventive controls are:

- ? Locks, fences, or guards that prevent unauthorized physical access to a facility or a device
- ? Firewalls, antivirus software, or encryption that prevent unauthorized logical access to a network or a system
- ? Policies, procedures, or training that prevent unauthorized or inappropriate actions or behaviors by users or employees

An AUP is an example of an administrative preventive control, because it defines the policies and procedures that users must follow to ensure the security and proper use of the network and the IT resources. An AUP can prevent users from engaging in activities that could compromise the security, performance, or availability of the network or the system, such as:

- ? Downloading or installing unauthorized or malicious software
- ? Accessing or sharing sensitive or confidential information without authorization or encryption
- ? Using the network or the system for personal, illegal, or unethical purposes
- ? Bypassing or disabling security controls or mechanisms
- ? Connecting unsecured or unapproved devices to the network

By enforcing an AUP, a company can prevent or reduce the likelihood of security breaches, data loss, legal liability, or reputational damage caused by user actions or inactions<sup>3</sup>.

References = 1: How to Create an Acceptable Use Policy - CoreTech, 2: [Security Control Types: Preventive, Detective, Corrective, and Compensating], 3: Why You Need A Corporate Acceptable Use Policy - CompTIA

#### NEW QUESTION 64

A user is attempting to patch a critical system, but the patch fails to transfer. Which of the following access controls is most likely inhibiting the transfer?

- A. Attribute-based
- B. Time of day
- C. Role-based
- D. Least privilege

**Answer: D**

#### Explanation:

The least privilege principle states that users and processes should only have the minimum level of access required to perform their tasks. This helps to prevent unauthorized or unnecessary actions that could compromise security. In this case, the patch transfer might be failing because the user or process does not have the appropriate permissions to access the critical system or the network resources needed for the transfer. Applying the least privilege principle can help to avoid this issue by granting the user or process the necessary access rights for the patching activity. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 931

#### NEW QUESTION 65

A company is developing a critical system for the government and storing project information on a fileshare. Which of the following describes how this data will most likely be classified? (Select two).

- A. Private
- B. Confidential
- C. Public
- D. Operational
- E. Urgent
- F. Restricted

**Answer: BF**

#### Explanation:

Data classification is the process of assigning labels to data based on its sensitivity and business impact. Different organizations and sectors may have different data classification schemes, but a common one is the following1:

? Public: Data that can be freely disclosed to anyone without any harm or risk.

? Private: Data that is intended for internal use only and may cause some harm or risk if disclosed.

? Confidential: Data that is intended for authorized use only and may cause significant harm or risk if disclosed.

? Restricted: Data that is intended for very limited use only and may cause severe harm or risk if disclosed.

In this scenario, the company is developing a critical system for the government and storing project information on a fileshare. This data is likely to be classified as confidential and restricted, because it is not meant for public or private use, and it may cause serious damage to national security or public safety if disclosed. The government may also have specific requirements or regulations for handling such data, such as encryption, access control, and auditing2. References: 1: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 16-17 2: Data Classification Practices: Final Project Description Released

#### NEW QUESTION 66

A systems administrator set up a perimeter firewall but continues to notice suspicious connections between internal endpoints. Which of the following should be set up in order to mitigate the threat posed by the suspicious activity?

- A. Host-based firewall
- B. Web application firewall
- C. Access control list
- D. Application allow list

**Answer: A**

#### Explanation:

A host-based firewall is a software application that runs on an individual endpoint and filters the incoming and outgoing network traffic based on a set of rules. A host-based firewall can help to mitigate the threat posed by suspicious connections between internal endpoints by blocking or allowing the traffic based on the source, destination, port, protocol, or application. A host-based firewall is different from a web application firewall, which is a type of firewall that protects web applications from common web-based attacks, such as SQL injection, cross-site scripting, and session hijacking. A host-based firewall is also different from an access control list, which is a list of rules that control the access to network resources, such as files, folders, printers, or routers. A host-based firewall is also different from an application allow list, which is a list of applications that are authorized to run on an endpoint, preventing unauthorized or malicious applications from executing. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 254

#### NEW QUESTION 69

.....

## **Thank You for Trying Our Product**

### **We offer two products:**

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### **SY0-701 Practice Exam Features:**

- \* SY0-701 Questions and Answers Updated Frequently
- \* SY0-701 Practice Questions Verified by Expert Senior Certified Staff
- \* SY0-701 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* SY0-701 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The SY0-701 Practice Test Here](#)**