



Fortinet

Exam Questions FCSS_LED_AR-7.6

FCSS - LAN Edge 7.6 Architect

NEW QUESTION 1

When the MAC address of a device is placed in quarantine on FortiSwitch, what happens to its egress traffic?

- A. Traffic is sent to an access VLAN.
- B. Traffic is assigned to the native VLAN.
- C. Traffic is sent as untagged traffic.
- D. Traffic is sent to an allowed VLAN.

Answer: A

NEW QUESTION 2

Connectivity tests are being performed on a newly configured VLAN. The VLAN is configured on a FortiSwitch device that is managed by FortiGate. During testing, it is observed that devices within the VLAN can successfully ping FortiGate. and FortiGate can also ping these devices. Inter-VLAN communication is working as expected. However, devices within the same VLAN are unable to communicate with each other. What could be causing this issue?

- A. Access VLAN is enabled on the VLAN.
- B. The FortiSwitch MAC address table is missing entries.
- C. The FortiGate ARP table is missing entries.
- D. The native VLAN configured on the ports is incorrect.

Answer: A

NEW QUESTION 3

A FortiSwitch is not appearing in the FortiGate management interface after being connected via FortiLink. What could be a first troubleshooting step?

- A. Ensure that the FortiGate security policies allow traffic from the FortiSwitch.
- B. Manually assign a static IP to the FortiSwitch.
- C. Verify that FortiGate device DHCP server is assigning an IP to the FortiSwitch.
- D. Ensure the FortiSwitch has internet access.

Answer: C

NEW QUESTION 4

Which statement about generating a certificate signing request (CSR) for a CER certificate is true?

- A. Inaccurate or missing fields in the CSR will prevent the CA from validating the request, leading to the rejection of the certificate and possible delays in the deployment process.
- B. If key fields like the common name (CN) and organization (O) are incorrect, the certification authority (CA) will still issue the certificate, but it may not be trusted by certain applications or systems that rely on accurate field information for validation.
- C. CSR fields are primarily used for internal recordkeeping by the requesting organization, and only the public key in the CSR must be accurate for successful certificate signing.
- D. The fields in the CSR are primarily for documentation purposes; any missing or incorrect information will be automatically corrected by the CA during the signing process.

Answer: A

NEW QUESTION 5

You are deploying a FortiSwitch device managed by FortiGate in a secure network environment. To ensure accurate communication, you must identify which protocols are required for communication and control between FortiGate and FortiSwitch.

Which three protocols are used by FortiGate to manage and control FortiSwitch devices? (Choose three.)

- A. SNMP can be used by FortiGate to manage FortiSwitch devices by monitoring their status.
- B. UHTTPS is used by FortiGate to securely manage and configure FortiSwitch devices.
- C. FortiGate uses the Fortilink protocol to establish communication with FortiSwitch.
- D. CAPWAP is used to establish the control channel between FortiSwitch and FortiGate.
- E. IGMP is required for managing communication between FortiGate and FortiSwitch devices in multicast environments.

Answer: BCD

NEW QUESTION 6

A conference center wireless network provides guest access through a captive portal, allowing unregistered users to self-register and connect to the network. The IT team has been tasked with updating the existing configuration to enforce captive portal authentication over a secure HTTPS connection. Which two steps should the administrator take to implement this change? (Choose two.)

- A. Enable HTTP redirect in the user authentication settings.
- B. Create a new SSID with the HTTPS captive portal URL.
- C. Disable HTTP administrative access on the guest SSID to enforce HTTPS connection.
- D. Update the captive portal URL to use HTTPS on FortiGate and FortiAuthenticator.

Answer: AD

NEW QUESTION 7

What is the primary function of FortiLink NAC in a LAN environment?

- A. To extend security policies across FortiGate firewalls only
- B. To automate device onboarding and verify security posture
- C. To manage FortiSwitch devices and apply manual firewall rules
- D. To ensure devices are manually placed in VLANs based on their user roles

Answer: B

NEW QUESTION 8

A network administrator connects a new FortiGate to the network, allowing it to automatically discover and register with FortiManager. What occurs after FortiGate retrieves the FortiManager address?

- A. FortiGate establishes a secure tunnel to FortiManager over TCP port 541.
- B. The device needs to be manually authorized on FortiManager.
- C. FortiGate configures its interface settings based on a DHCP response from FortiManager.
- D. FortiGate sends a discovery request to all devices on the local network using UDP port 1068.

Answer: A

NEW QUESTION 10

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questons and Answers in PDF Format

FCSS_LED_AR-7.6 Practice Exam Features:

- * FCSS_LED_AR-7.6 Questions and Answers Updated Frequently
- * FCSS_LED_AR-7.6 Practice Questions Verified by Expert Senior Certified Staff
- * FCSS_LED_AR-7.6 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * FCSS_LED_AR-7.6 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The FCSS_LED_AR-7.6 Practice Test Here](#)